

ENFOCUS



**PITSTOP
SERVER²⁴**

Command Line Interface

Contents

1. Introduction.....	5
1.1. Short summary.....	5
1.2. Objectives.....	5
1.2.1. Target group.....	5
1.2.2. Ease of use.....	5
1.2.3. Distribution.....	6
1.2.4. Multiple invocations.....	6
2. The Command Line Interface.....	7
2.1. Command line options.....	7
2.1.1. Syntax.....	7
2.1.2. Overview.....	7
2.1.3. Configuration.....	8
2.1.4. Process and ExportImage options.....	9
2.1.5. Task report.....	11
2.1.6. Admin.....	11
2.1.7. Use cases.....	12
2.2. Exit behavior.....	12
2.2.1. Exit code.....	12
2.2.2. Error message.....	12
2.2.3. Error codes.....	13
2.3. Default values.....	13
2.3.1. General rule.....	13
2.3.2. System fonts.....	13
3. Configuration XML file.....	14
3.1. Introduction.....	14
3.1.1. Ordering of XML elements.....	14
3.1.2. Unicode support.....	14
3.1.3. XML namespace and schema.....	14
3.1.4. PathType.....	14
3.2. Configuration.....	15
3.3. Versioning.....	16
3.4. Initialize.....	16
3.4.1. Other information.....	17
3.5. TaskReport.....	17
3.5.1. QueryMutatorDB.....	19
3.5.2. QueryMutatorInfo.....	19
3.6. Process.....	20
3.6.1. InputPDF.....	22

3.6.2. InputImage.....	22
3.6.3. OutputPDF.....	23
3.6.4. Reports.....	24
3.6.5. Flattening.....	25
3.6.6. Mutators.....	28
3.6.7. SmartPreflight.....	28
3.6.8. CertifiedPDF.....	28
3.6.9. ColorManagement.....	30
3.6.10. Fonts.....	33
3.7. ExportImage.....	34
3.7.1. InputPDF.....	35
3.7.2. OutputImages.....	35
3.7.3. RenderOptions.....	37
3.7.4. ActionLists.....	40
3.7.5. SmartPreflight.....	40
3.7.6. ColorManagement.....	41
3.7.7. Fonts.....	43
4. Task Report XML file.....	45
4.1. Introduction.....	45
4.1.1. Unicode support.....	45
4.1.2. XML namespace and schema.....	45
4.1.3. PathType.....	45
4.2. TaskReport.....	46
4.2.1. VersionInfo.....	47
4.2.2. SupportInfo.....	48
4.2.3. CommandLine.....	48
4.2.4. ProcessResults.....	48
4.2.5. ImageExportResults.....	49
4.2.6. Errors.....	49
4.2.7. Languages.....	50
4.2.8. MutatorDB.....	50
4.2.9. MutatorInfo.....	51
5. Task identifiers.....	52
5.1. Introduction.....	52
5.1.1. Logical order.....	52
5.1.2. Task identifiers.....	52
5.1.3. XML namespace.....	52
5.1.4. Empty value.....	52
5.2. Supported elements.....	53
6. Appendix.....	54
6.1. Example Configurations.....	54
6.1.1. Flattening a PDF.....	54

6.1.2. Retrieving Preflight Profile information.....54

6.1.3. Converting a PDF to images.....55

6.1.4. Validating a PDF against a GWG Profile.....56

6.1.5. Processing image input.....56

6.1.6. Full Configuration (Windows).....57

6.1.7. Full Configuration (Mac)..... 61

7. Third-Party License Information..... 66

8. Copyrights..... 83

1. Introduction

1.1. Short summary

This document specifies a command line interface for PitStop Server, shipped as part of the standard product.

Compared to the standard product, the CLI version provides some extra functionality: in addition to file processing, it allows you to render the pages of a PDF to images, either as a whole or split into separations. Also, it's possible to input images, which will be converted to PDF before further processing. This functionality is not yet available in the standard product; for the time being, image input is only supported in the CLI and in the PitStop Server Configurator.

1.2. Objectives

1.2.1. Target group

System integrators (including sophisticated end-users) form the main target group for the PitStop Server Command line interface (CLI).

Integrators often want to use PitStop technology in a convenient way without using the C programming language. They may lack the C programming skills or they may need to invoke PitStop from a scripted environment.

1.2.2. Ease of use

The CLI is identical on all supported platforms. Options are specified as command-line arguments and in a configuration file passed to the command line. Advanced options can be omitted. Simple processing can even be achieved without a configuration file.

If PitStop Server is running while processing files through the CLI, the PitStop Server user interface can be used to check the CLI jobs. Just like for the regular hot folder jobs, you can for example:

- Check which files are being processed (in the Hot folder tab) or have been processed earlier (in the History tab)
- Follow up on the job progress (in the Progress folder tab)
- Generate statistics (via the Statistics button in the History tab)
- ...



Note: The PDF2Image functionality is only available in the CLI version, hence cannot be monitored through the standard PitStop Server user interface. That is also the case for the image to PDF conversion.

1.2.3. Distribution

The CLI is implemented as an independent executable, which is part of PitStop Server. On Mac the CLI is installed inside the PitStop Server package, on Windows next to all other executables.

The CLI finds its resources without relying on the PATH environment variable or regardless of the working folder from which the CLI is called.

The CLI is only supported in combination with “its” PitStop Server installation. If PitStop Library is replaced or resources are added or removed, there are no guarantees on its behavior. Like in the regular PitStop Server product we do not verify that the installation is unmodified and we try to give reasonable error messages if something goes wrong, but most error messages will be cryptic and sometimes the system could even crash.

The CLI knows where to find PitStop Library and its resources.

1.2.4. Multiple invocations

Multiple invocations of the CLI can execute concurrently. Each invocation creates a unique temporary location for PitStop Library and removes the temporary data on exit.

2. The Command Line Interface

The Command Line Interface is the same on all platforms.

2.1. Command line options

2.1.1. Syntax

The arguments on the command line are of the form:

–key [value]

with following restrictions:

- Keys are case-insensitive.
- Values that contain spaces are enclosed in double quotes (") on Windows. On Mac there are 3 conventions: enclose in double quotes or single quotes ('), or precede the space with a backslash (\<space>). All three conventions are supported.
- Paths are in platform syntax (Posix notation on Mac) and either absolute or relative to the current working directory.

Example

Windows:

- "C:\Program Files\Enfocus\Enfocus PitStop Server 24\PitStopServerCLI.exe" -input "C:\Program Files\Enfocus\Enfocus PitStop Server 24\Help\Enfocus PitStop Server CLI (enUS).pdf" -mutator "C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\Action Lists\Add\Add Penguin.eal" -output "C:\output.pdf" -reportPDF "C:\report.pdf"

Mac:

- "/Applications/Enfocus/Enfocus PitStop Server 24/PitStopServerCLI" -input "/Applications/Enfocus/Enfocus PitStop Server 24/Help/Enfocus PitStop Server CLI (enUS).pdf" -mutator "/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/Action Lists/Add/Add Penguin.eal" -output ~/Desktop/output.pdf -reportPDF ~/Desktop/report.pdf

For more information about the command line options, refer to [Overview](#) on page 7.



Note: Example configuration files can be found at the end of this document ([Example Configurations](#) on page 54).

2.1.2. Overview

PitStopServerCLI

[–config <file path to a configuration file>]

[–input <file path to an input file>]

[mutator <file path to a Preflight Profile or an Action List>]
[-reportPDFTmpl <file path to a Report Template (incl. filename with extension .prefs)>]
[-output <file path to an output location (incl. filename)>]
[-reportPDF <file path to a report location (incl. filename)>]
[-reportXML <file path to a report location (incl. filename)>]
[-reportJSON <file path to a report location (incl. filename)>]
[-outputImage <filename or full path to an output location for the output images>]
[-imageType <output file type: JPEG, PNG or TIFF>]
[-taskReport <file path to a task report file (incl. filename)>]
[-imageInput]
[-imageInputResolution <resolution in ppi>]
[-imageInputWidth <width in points>]
[-imageInputHeight <height in points>]
[-version]
[-libraryVersion]
[-help]

None of these options is required (but at least one option has to be provided).

The order in which options are specified is irrelevant (with a minor exception for [admin](#) options).

2.1.3. Configuration

Key name	Value type	Description
config	Path (in)	Location and name of a configuration XML file with settings to configure PitStop Server CLI tasks. The format of the configuration file is described in a separate chapter. See Configuration XML file on page 14.

The configuration file is an XML file describing the task(s) to be executed with detailed settings. If no configuration file is specified, defaults* are used for all settings. In that case, at least the input option should be specified along with the mutator, output and/or report options (or nothing meaningful will happen).

* The CLI uses the same defaults as a clean installation of PitStop Server, and is not dependent on any PitStop Server preferences. For example, if no configuration file is specified, the default PitStop Server color management settings will be used.

2.1.4. Process and ExportImage options

These options specify the input and output paths used by the CLI for processing a PDF file or for rendering it to images. Any pre-existing file at an output location is overwritten.

If a configuration file is specified that contains one or more Process and/or ExportImage elements, a value on the command line (for one of the above options) overrides the corresponding value in the first Process or ExportImage element. In other words, the value in the configuration file is ignored.

This rule applies to each value individually. For example, specifying an input file on the command line does not affect the mutator(s) specified in the Process or ExportImage element. However, a mutator specified on the command line does override all mutators specified in the first Process or ExportImage element.

Any subsequent Process/ExportImage elements (other than the first one) in the configuration file are not affected by the command line options.

Key name	Value type	Description
input	Path (in)	Location and name of the input file. This can be a PDF or an image file. In case of an image, the <code>imageInput</code> option must be added to the command line, to convert the image to PDF before running a Preflight Profile or an Action List. Supported image file formats: - JPEG (CMYK, RGB, Grayscale)  Note: JPEG2000 is not supported. - PNG (RGB, Grayscale, also files with embedded ICC Profile)  Note: Transparency in PNG files is converted to PDF transparency. Indexed colors are not (yet) supported; such images will trigger an error.
mutator	Path (in)	Location and name of a file containing a Preflight Profile or an Action List.
output	Path (out)	Location and name for the output PDF file. It is acceptable for this to be the same path as the input path (i.e. a file can be processed “in place”).

Key name	Value type	Description
reportPDF	Path (out)	Location and name for the PDF report file (regular or annotated report).
reportPDFTmpl	Path (in)	Location and name of the report template for creating the report.  Note: The report template is a file with extension <i>.prefs</i>. For more information, refer to the PitStop Custom Report Templates guide on the Enfocus web site. This value is ignored if no reportPDF path is specified.
reportXML	Path (out)	Location and name for the XML report file.
reportJSON	Path (out)	Location and name for the JSON report file.
outputImage	Path (out)	Path to an image file.
imageType	Path (out)	File type of the output image (JPEG, PNG or TIFF).
imageInput	-	Enable the image to PDF conversion. The size of the generated PDF depends on image metadata. Only if the image metadata does not contain info about the size of the file (physical dimensions, physical size, density), the specified resolution (imageInputResolution) or the specified width (imageInputWidth) and/or height (imageInputHeight) are used to determine the size of the image.  Note: - When using a configuration file, it's possible to override the image metadata by setting <code>PageSizeOverridesImageMetadata</code> to false. In that case, the given resolution and dimensions are used. This option is not available when using the command line. For an example configuration file, see Processing image input on page 56. - If both the resolution and the dimensions are specified, the resolution will be applied and the dimensions will be ignored. - Note that the options for resolution, height and width only change the print resolution or the print size, not the pixel count of the image. Resampling the image in the

Key name	Value type	Description
		PDF, changing its compression, etc. can be done afterwards with a PitStop Action.
imageInputResolution	Path (in)	Resolution (in ppi) to use when converting an image to PDF.
ImageinputWidth	Path (in)	Width (in points) to use when converting an image to PDF.
ImageinputHeight	Path (in)	Height (in points) to use when converting an image to PDF.

2.1.5. Task report

Key name	Value type	Description
taskReport	Path (out)	Location and name of a task report XML file, with information on the tasks executed by the CLI Any pre-existing file at the location is overwritten. The format of the task report file is described in a separate chapter. See Task Report XML file on page 45.

If a configuration file is specified that contains a TaskReport element, the value for the taskReport option on the command line overrides the TaskReportPath value in the TaskReport element. In other words, the value in the configuration file is ignored.

2.1.6. Admin

Key name	Value	Description
version	none	Write the CLI version to stdout
libraryVersion	none	Write the PitStop Library version to stdout
help	none	Write an English summary of the command line options to stdout (see Overview on page 7)

These options cause low-ASCII text to be written to stdout. The version and libraryVersion options produce a single line that can be easily interpreted by another application (in addition to being readable for humans).

If an admin option is specified, all non-admin options are ignored. If multiple admin options are specified, they are processed in order of occurrence on the command line.

2.1.7. Use cases

Options may be meaningfully combined as follows:

Options specified	Description	Use case
A single admin option	Produce output on stdout	Verify version number Get help on options
Just input/output options (no config file)	Use default settings for simple processing	Produce a Preflight Report for a PDF file Run an Action List on a PDF file
Just the config option	All settings are specified in the configuration file, including input and output paths	An automated system generates a configuration file with specific settings for every job
The config option plus input/output options	Most settings are in the configuration file, and some input/output paths are overruled on the command line	The configuration file is created once (perhaps by hand); it serves as a fixed template for all jobs

2.2. Exit behavior

2.2.1. Exit code

The exit code of the CLI is zero when the task is successful and non-zero when there is a fatal problem (see [Error codes](#) on page 13).

Note that Preflight errors or warnings do not cause the CLI to return a non-zero exit code; these issues are listed in the Preflight Report or in the CLI's task report.

2.2.2. Error message

If the CLI exits with a nonzero exit code, it writes an appropriate error message to stderr with the following characteristics:

- It starts with a decimal representation of an error code (see [Error codes](#) on page 13), followed by a colon, and followed by a human-readable message describing the problem in as much detail as possible.

- It is in English (enUS) and uses UTF-8 encoding (so that filenames can always be interpreted correctly).
- It is on a single line and it is the last nonempty line written to stderr.

2.2.3. Error codes

Exit code Windows	Exit code Mac	Description	Error code written to stderr
0	0	Successful operation	Not applicable
-1	255	Problem with command line arguments or configuration file settings detected by the CLI	Error code specific to the CLI These error codes are chosen so that they don't clash with those of PitStop Library
-2	254	Unexpected error returned by PitStop Library	PitStop Library error code

2.3. Default values

The default value for each setting is discussed in the chapter on the configuration file (See [Configuration XML file](#) on page 14).

2.3.1. General rule

As a general rule, the default value for PitStop Server CLI settings is the default value used by PitStop Server after a clean installation. The CLI does not rely on the PitStop Server preferences. For example the default temporary location is the operating system default (temp folder for the current user) even if the PitStop Server preferences are set to use a specific folder.

However, if jobs are processed through the running instance of PitStop Server, some settings, such as the temp folder, are used for the parts of the job that are done by PitStop Server.

2.3.2. System fonts

By default PitStop Server CLI loads all system fonts before processing a PDF file. Depending on the number of available fonts, this may consume substantial processing time and resources.

In situations where the system fonts aren't used, one should use the appropriate setting in the configuration file to avoid loading them.

3. Configuration XML file

3.1. Introduction

The configuration file provides detailed instructions and settings for the command line tool. It is constructed as a tree of XML elements. The remaining sections in this chapter describe each element that may appear in the file and its immediate child elements.

3.1.1. Ordering of XML elements

The elements in the configuration file must be ordered to allow single-pass parsing. In other words, all information necessary to execute a certain task must be presented before the command requesting the task.

The description for each element specifies the ordering requirements for its immediate children, if there are any such requirements. The tables always list elements in a “safe” order; in other words ordering elements as presented in the tables never violates the ordering requirements.

3.1.2. Unicode support

The configuration file is a well-formed XML document, which means that it fully supports Unicode for text values such as filenames. If the text encoding specified in the XML header is not understood, the job fails.

3.1.3. XML namespace and schema

XML namespace	http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd
Preferred prefix	cf (or use default namespace)
Schema definition	PitStopServerCLI_Configuration.xsd

3.1.4. PathType

This is a string type representing a file or folder path. Both absolute and relative paths are supported.

An absolute path must be specified in the native platform format, for example:

- On Windows: C:\Preflight\Input\input.pdf
- On Mac: /Volumes/Preflight/Input/input.pdf

A relative path is interpreted relative to the CLI's current working directory and can be specified with forward or backward slashes on all platforms. This allows a configuration file with only relative paths to be platform-independent. For example the following two paths have the same meaning on all platforms:

- Windows style: `..\Input\input.pdf`
- Mac style: `../Input/input.pdf`

3.2. Configuration

This is the root element of the configuration file. This element's children, if present, must be ordered exactly as presented in the table. Only the Process and ExportImage element may occur more than once and the order in which they are presented may vary.

Element name	Type	Multiplicity	Description
Versioning	Versioning	required	The version of this configuration file and the strategy to follow when PitStop Server CLI encounters settings it does not understand.
Initialize	Initialize	optional	Initialization settings.
TaskReport	TaskReport	optional	Settings for producing a task report. If no task report element is provided, and there is no task report option on the command line, no task report is generated.
Process	Process	zero or more	Requests for processing PDF files (e.g. performing Preflight and/or running Action Lists). Certain command line options override settings in the first Process or ExportImage element (or in a virtual default Process or ExportImage element if none is provided). If no Process elements are provided, and there are no process options on the command line, no processing occurs.
ExportImage	ExportImage	zero or more	Requests for rendering pages from PDF files to separate images. Certain command line options override settings in the first Process or ExportImage element (or in a virtual default Process or ExportImage element if none is provided). If no ExportImage elements are provided, and there are no ExportImage options on the command line, no image creation occurs.

3.3. Versioning

This element specifies the version of the XML config file, and how to react to unknown settings.

Element name	Type	Multiplicity	Description
Version	integer	required	The version of this XML configuration file. PitStop Server 24.11 introduced version 15.
VersioningStrategy	enumeration	optional	The strategy to follow when an unsupported setting is encountered: • BestEffort (default): ignore setting or substitute a reasonable value • MustHonor: exit with an error code

3.4. Initialize

This element specifies how the CLI should organize itself internally.

Element name	Type	Multiplicity	Description
TempPath	<i>PathType</i>	optional	Path to the folder in which all temporary files should be stored. The default temporary location is the operating system default (temp folder for the current user). It is acceptable to specify the same path for multiple concurrent invocations of the CLI.
ProcessingMethod	enumeration	optional	A file can be preflighted in two ways: either by the CLI (internally) or by PitStop Server as a rush job. • If PreferServer is selected • And PitStop Server is running, PitStop Server will process the file. • And PitStop Server is NOT running, the CLI will process the file. • If EnforceInternal is selected, the CLI will process the file.

Element name	Type	Multiplicity	Description
ShutDownServerAtExit	boolean	optional	If EnforceServer is selected, PitStop Server will process the file.
			 Note: This option is only relevant for "Process" jobs; it does not apply to PDF2Image conversion and it has no impact on the querying options in the TaskReport, which are generated internally.
ShutDownServerAtExit	boolean	optional	If present and true, the server will be shut down before the CLI shuts down. This means that all relevant PitStop Server processes will be started and stopped for each processed file.

3.4.1. Other information

The CLI passes the appropriate information to PitStop Library for:

- Product info used in PDF reports
- System info for Certified PDF
- Registration info for Certified PDF

This information can't be changed by the user.

3.5. TaskReport

This element specifies a request to generate a task report, including the settings to define the report's contents. The TaskReportPath element must be placed first; the order of the other children may vary and determines the order in which the responses occur in the task report.

Element name	Type	Multiplicity	Description
TaskReportPath	<i>PathType</i>	required	The location and filename where the requested task report should be placed.
LogVersionInfo	boolean	optional	If present and true, the task report contains version information on the PitStop Server CLI and its PitStop Library.

Element name	Type	Multiplicity	Description
LogSupportInfo	boolean	optional	If present and true, the task report contains information useful for support and debugging purposes. Use this option only when requested by Enfocus technical support.
LogCommandLine	boolean	optional	If present and true, the task report contains a list of the options received (and recognized) on the command line.
LogProcessResults	boolean	optional	If present and true, the task report contains the number of errors, warnings, fixes, signoffs, failures and critical failures for each Process task.
LogExportImageResults	boolean	optional	If present and true, the task report contains a list of the paths of the generated images, the matching page and, if applicable, the separation name.
LogErrors	boolean	optional	If present and true, the task report contains a list of warning and error messages encountered during execution.
QueryLanguages	boolean	optional	If present and true, the task report contains a list of the languages supported by PitStop Server CLI.
QueryCMMs	boolean	optional	If present and true, the task report contains a list of CMMs supported by PitStop Server CLI.
QueryDefaultProfileDB	QueryMutatorDB	optional	Requests a list of the Preflight Profiles in the default database to be included in the task report.
QueryLocalProfileDB	QueryMutatorDB	optional	Requests a list of the Preflight Profiles in the local database to be included in the task report.
QueryDefaultActionDB	QueryMutatorDB	optional	Requests a list of the Action Lists in the default database to be included in the task report.

Element name	Type	Multiplicity	Description
QueryLocalActionDB	QueryMutatorDB	Optional	Requests a list of the Action Lists in the local database to be included in the task report.
QueryMutatorInfo	QueryMutatorInfo	zero or more	Requests information on a mutator, i.e. a Preflight Profile or an Action List, to be included in the task report.

3.5.1. QueryMutatorDB

These elements specify a request for getting a list of mutators in one of the databases managed by PitStop Server (the default and local Preflight Profile and Action Lists databases).

The path of each mutator is always listed. Additional information can be requested by specifying one or more child elements.

Element name	Type	Multiplicity	Description
MutatorInfoOptions	enumeration	zero or more	The type of information requested; one of: - Name: the name of the mutator - Company: the company of the author of the mutator - Author: the author of the mutator - Description: the description of the mutator - MutatorType: the type of mutator (Preflight Profile or Action List) - DateTime: the most recent modification date and time of the mutator - Version: the version of the mutator - IsFullyUnderstood: check if PitStop Server CLI fully supports all settings and instructions in this mutator - IsVersionCorrect: check if the version of the mutator is correct - IsConfigurationCorrect: check if the configuration of the mutator is correct - IsUsableAsRestriction: check if the mutator can be used as restricting Action List

3.5.2. QueryMutatorInfo

This element specifies a request for getting information on a mutator, i.e. a Preflight Profile or an Action List.

Element name	Type	Multiplicity	Description
MutatorPath	<i>PathType</i>	required	The path to the mutator (Preflight Profile or Action List) for which information is being requested
MutatorInfoOptions	enumeration	zero or more	The type of information requested; one of: - Name: the name of the mutator - Company: the company of the author of the mutator - Author: the author of the mutator - Description: the description of the mutator - MutatorType: the type of mutator (Preflight Profile or Action List) - DateTime: the most recent modification date and time of the mutator - Version: the version of the mutator - IsFullyUnderstood: check if PitStop Server CLI fully supports all settings and instructions in this mutator - IsVersionCorrect: check if the version of the mutator is correct - IsConfigurationCorrect: check if the configuration of the mutator is correct - IsUsableAsRestriction: check if the mutator can be used as a restricting Action List

3.6. Process

This element specifies a request for processing a PDF file (e.g. performing Preflight or running Action Lists). There can be multiple Process elements.

Element name	Type	Multiplicity	Description
InputPDF	<i>InputPDF</i>	optional (*)	Location of the input PDF file (*) is in fact required, but for the first Process element may be specified as a command-line option.
InputImage	<i>InputImage</i> on page 22	optional (*)	Location of the input image that will be converted to PDF first, before further processing. (*) is in fact required, but for the first Process element may be specified as a command-line option.
OutputPDF	<i>OutputPDF</i>	optional (*)	Location and settings for the output PDF file

Element name	Type	Multiplicity	Description
			(*) is in fact required, but for the first Process element may be specified as a command-line option.
Reports	<i>Reports</i>	optional	Type and location of reports to be created If no reports are specified here or (for the first Process element) on the command-line, none are generated.
Flattening	<i>Flattening</i>	optional	Settings for the flattening. If this setting is not defined, no flattening will be performed.
Mutators	<i>Mutators</i>	optional	Location of Preflight Profile or Action List to be used. If no mutators are specified here or (for the first Process element) on the command-line, none are used.
SmartPreflight	<i>SmartPreflight</i>	optional	Location of Variable Set and Job Ticket to be used. If no SmartPreflight is defined, preflight is executed without Smart Preflighting.
CertifiedPDF	<i>CertifiedPDF</i>	optional	Settings for Certified PDF behavior
ColorManagement	<i>ColorManagement</i>	optional	Settings for color management
Fonts	<i>Fonts</i>	optional	Settings for font management
Language	enumeration	optional	The language to be used in the Preflight Report as a 4-character string in the form 'enUS', 'frFR', 'deDE', ... If the requested language is not available, English (enUS) is used instead. The default language is English (enUS).
MeasurementUnit	enumeration	optional	The measurement unit to be used in the Preflight Report; one of: • Point (the default) • Pica • Inch

Element name	Type	Multiplicity	Description
			• Foot • Millimeter • Centimeter • Meter

3.6.1. InputPDF

This element specifies the location of an input PDF file.

Element name	Type	Multiplicity	Description
InputPath	<i>PathType</i>	optional (*)	Path to the input PDF file (*) is in fact required, but for the first Process/ExportImage element may be specified as a command-line option.

3.6.2. InputImage

This element specifies the location and the preferred size of an input image file.

Element name	Type	Multiplicity	Description
InputPath	<i>PathType</i>	optional (*)	Path to the input image file. (*) is in fact required, but for the first Imageinput element may be specified as a command-line option.
PageSize	<i>PageSize</i>	optional	Requested page size.
PageSizeOverridesImageMetadata	boolean	zero or one	If present and true, the given page size overrides the size info in the image metadata.

3.6.2.1. PageSize

This element specifies the requested page size when converting an image file to PDF.

Element name	Type	Multiplicity	Description
Width	integer	optional (*)	If the size info in the image metadata is ignored by setting PageSizeOverridesImageMetadata to True, the given width is used to convert the image to PDF. The length is not

Element name	Type	Multiplicity	Description
			needed, because the aspect ratio of the original image is kept. (*) Only if PageSizeOverridesImageMetadata is set to True, this option is mandatory.

3.6.3. OutputPDF

This element specifies the location and save options for the output PDF file.

Element name	Type	Multiplicity	Description
OutputPath	PathType	optional (*)	Path for the output PDF file (*) is in fact required, but for the first Process element may be specified as a command-line option.
SaveOptions	SaveOptions	optional	Save options for the output PDF file.

3.6.3.1. SaveOptions

This element specifies save options for the output PDF file.

Element name	Type	Multiplicity	Description
PerformFullSave	boolean	optional	If true (the default), a full save is performed which means it is no longer possible to roll back Certified PDF sessions. If false, an incremental save is performed.
Optimization	enumeration	optional	Set the optimization option as one of: - Disabled: no optimization is performed. - FileSize: the internal structure is optimized to create the smallest possible PDF file. - WebDownload: the file will be optimized for usage on the web.

Element name	Type	Multiplicity	Description
			The default value is "FileSize".

3.6.4. Reports

This element specifies which reports should be created when processing a PDF file.

Element name	Type	Multiplicity	Description
ReportPDF	ReportPDF	zero or more	Settings for creating a PDF report
ReportXML	ReportXML	optional	Settings for creating an XML report
ReportJSON	ReportJSON	optional	Settings for creating a JSON report

3.6.4.1. ReportPDF

This element specifies settings for creating a PDF Report.

Element name	Type	Multiplicity	Description
ReportPath	PathType	required	Location and name for the generated Report file.
ReportTemplatePath	PathType	optional	Path to a PitStop Preflight Report template; if no template is specified, the regular Enfocus Preflight Report template is used.

3.6.4.2. ReportXML

This element specifies settings for creating an XML Report.

Element name	Type	Multiplicity	Description
ReportPath	PathType	required	Location and name for the generated Report file.
Version	Integer	Optional	The version of the XML Report. This can be 2 or 3.
MaxReportedNb ItemsPerCategory	Integer	Optional	The number of reported items per category in the Report is truncated to this value. If set to -1, no truncation is performed.

Element name	Type	Multiplicity	Description
MaxReportedNb OccurrencesPerItem	Integer	Optional	The number of occurrences per item in the Report is truncated to this value. If set to -1, no truncation is performed.

3.6.4.3. ReportJSON

This element specifies settings for creating a JSON Report.

Element name	Type	Multiplicity	Description
ReportPath	<i>PathType</i>	required	Location and name for the generated Report file.
MaxReportedNb ItemsPerCategory	Integer	Optional	The number of reported items per category in the Report is truncated to this value. If set to -1, no truncation is performed.
MaxReportedNb OccurrencesPerItem	Integer	Optional	The number of occurrences per item in the Report is truncated to this value. If set to -1, no truncation is performed.

3.6.5. Flattening

This element specifies which settings are to be used when a document is flattened. If preflighting is enabled by defining at least one Preflight Profile or Action List, flattening is performed before preflighting the PDF. It is possible to do flattening without preflighting. Flattening requires that Color Management is enabled.

Element name	Type	Multiplicity	Description
RasterVectorBalance	integer	zero or one	The raster/vector balance: a value from 0 to 100. This controls the degree of rasterization of complex areas in the document. If set to 100, no areas in the document will get rasterized for performance reasons (although some areas may still be rasterized for other reasons). The default is 100.
VectorResolution	integer	zero or one	The resolution for rasterizing vectors, text, and gradients. This is a value from 1 to 9600. The default is 1200.
GradientResolution	integer	zero or one	The resolution for gradients and Illustrator mesh objects after

Element name	Type	Multiplicity	Description
			rasterization because of flattening. This is a value from 1 to 1200. The default is 300.
ConvertAllText	boolean	zero or one	If present and true, all strokes are converted to filled paths.
ConvertAllStrokes	boolean	zero or one	If present and true, all text is converted to outlines and all type glyph information is discarded.
ClipComplexRegions	boolean	zero or one	If not present or true, this option ensures that the boundaries between vector artwork and rasterized artwork fall along object paths. This option reduces stitching artifacts as a result of a part of an object being rasterized while another part of the object remains in vector form.
PreserveOverprint	boolean	zero or one	If not present or true, overprint is preserved where possible. If this option is disabled all overprint in the document will be simulated by blending the colors of overprinted objects.
BlendingColorspace	PathType	zero or one	The attribute "Type" defines which kind of blending color space to use. Type can be • Current (the default): use the current blending color space if present. • None: don't use a blending color space • DeviceGray • DeviceRGB • DeviceCMYK • ICCProfile: A custom ICC profile The path in the element should point to a valid ICC profile in case "ICCProfile" is chosen, and can be left empty otherwise.
RemoveICCPProfiles	boolean	zero or one	If not present or true, the ICC profiles are removed after flattening.

Element name	Type	Multiplicity	Description
ImageCompression	ImageCompression	zero or one	Settings for the post flattening image recompression. If not present, images are not recompressed as part of the flattening.

3.6.5.1. ImageCompression

This element specifies the options to be used when recompressing the images after flattening.

Element name	Type	Multiplicity	Description
Color	enumeration	zero or one	Recompress the color bitmap images with the given compression technique. Valid values are • ZIP4bit • ZIP8bit • JPEGMinimum • JPEGLow • JPEGMedium (the default) • JPEGHigh • JPEGMaximum.
Grayscale	enumeration	zero or one	Recompress the grayscale bitmap images with the given compression technique. Same valid values as for "Color" (see above)
OneBit	enumeration	zero or one	Recompress the one bit bitmap images with the given compression technique. Valid values are • ZIP • CCITTGroup3 (the default) • CCITTGroup4 • RunLength
ASCIIFilter	enumeration	zero or one	The settings for applying an ASCII filter. Valid values are • None (the default) • ASCIIHex

Element name	Type	Multiplicity	Description
			ASCII85

3.6.6. Mutators

This element specifies the mutators that should be used for processing the PDF file. Any number of Action Lists and at most one Preflight Profile can be specified. The Actions Lists are executed in the same order as the XML elements; the Preflight Profile is always executed last.

If a mutator is specified on the command line, any and all mutators listed in the first Process element are ignored.

Element name	Type	Multiplicity	Description
ActionList	<i>PathType</i>	zero or more	Path to an Action List file
PreflightProfile	<i>PathType</i>	optional	Path to a Preflight Profile file

3.6.7. SmartPreflight

This element specifies the settings that should be used for Smart Preflighting the PDF file. One Variable Set and at most one Job Ticket can be specified. Whether or not the contents of the Job Ticket is used is defined by the Variable Set.



Note: For detailed information about Smart Preflight, please refer to the PitStop Server Reference Guide.

Element name	Type	Multiplicity	Description
VariableSet	<i>PathType</i>	required	Path to a Variable Set file
JobTicket	<i>PathType</i>	zero or one	Path to a Job Ticket file

3.6.8. CertifiedPDF

This element specifies settings related to Certified PDF processing.

Element name	Type	Multiplicity	Description
CertifiedPDFAction	enumeration	optional	The Certified PDF action; one of: MakeCertified: always output a Certified PDF file (even if the input is not).

Element name	Type	Multiplicity	Description
			- MakeUncertified: remove any Certified PDF information when saving the output file. - KeepStatusUnchanged: incoming Certified PDF documents remain certified; incoming non-Certified PDF documents remain uncertified. If a Preflight Profile is specified for this process, the default is "MakeCertified"; otherwise the default is "KeepStatusUnchanged".
KeepOriginalProfile	boolean	optional	The value of this setting is used only if a Preflight Profile is specified for this process. If true, and the incoming Certified PDF file has an embedded Preflight Profile, that profile is used for performing the preflight step instead of the Preflight Profile specified for this process. If false (default), any embedded Preflight Profile is removed and replaced by the Preflight Profile specified for this process.
UserInfo	<i>UserInfo</i>	optional	Information on the user performing this operation; stored in the Certified PDF data.
SessionComment	string	required	Description of the operation being performed; stored in the Certified PDF data.

3.6.8.1. UserInfo

This element specifies information on the user performing this operation. This information is stored in the PDF file as part of the Certified PDF data.

Element name	Type	Multiplicity	Description
Name	string	optional	User name and contact information.
Company	string	optional	Default value is an empty string for all fields.
Street	string	optional	

Element name	Type	Multiplicity	Description
City	string	optional	
State	string	optional	
Country	string	optional	
PostalCode	string	optional	
Phone	string	optional	
Fax	string	optional	
Email	string	optional	
Message	string	optional	Comments that may help identify the user or otherwise assist in the Certified PDF workflow. Default value is an empty string.

3.6.9. ColorManagement

This element specifies settings related to color management.

Color management can be configured separately for images and all other objects (text, line art), or for all objects (including images) at the same time.

If color management is not turned on for a particular object type, the corresponding source and target ICC profiles are ignored.

Element name	Type	Multiplicity & Description
AllObjects	<i>ColorManagementSettings</i>	Only the following combinations are allowed: - Just “AllObjects”: specify the same color management options for all objects in the file - Both “Images” and “OtherObjects”: specify separate color management options for images and for non-images (text & line-art) - None of these elements: use the default settings for all objects in the file
Images		
OtherObjects	<i>ColorManagementSettings</i>	

Element name	Type	Multiplicity & Description
UseBlackPoint Compensation	boolean	If present and true, Black Point Compensation will be used. Note that this option is only available if color management is enabled.

3.6.9.1. ColorManagementSettings

This element specifies color management settings for a particular category of objects.

Element name	Type	Multiplicity	Description
Enabled	boolean	optional	If true (default), color management is enabled. If false, the remaining settings in this list are ignored.
RenderingIntent	enumeration	optional	The output rendering intent; one of: - ObjectDefined (default): the rendering intent of the object itself, as shown on the prepress tab of the PitStop Inspector - Relative: in-gamut colors are reproduced exactly; out-of-gamut colors are mapped to the nearest value within the reproducible gamut; corrections are made for the output medium's white point. - Absolute: in-gamut colors are reproduced exactly; out-of-gamut colors are mapped to the nearest value within the reproducible gamut; no correction is made for the output medium's white point. - Saturation: colors are represented in a manner that preserves or emphasizes saturation. - Perceptual: colors are represented in a manner that provides a pleasing perceptual appearance.
SourceICCPProfiles	ICCPProfiles	optional (*)	The source ICC profiles (*) Required if color management is enabled

Element name	Type	Multiplicity	Description
SourceOutputIntent OverridesICCProfiles	boolean	optional	If true, the rendering intent overrides the selected ICC profile rendering intent for the source ICC profiles The default value is false
TargetICCProfiles	<i>ICCProfiles</i>	optional	The target ICC profiles. If not provided, the source ICC profiles are used as target ICC profiles as well.  Note: Target ICC profiles set for non-images are only used for pre-rendering. For example, for color conversions (using a pre-render Action List, as the first step of the processing), you can use different profiles for images and other objects. However, to render the PDF to images, the <i>target ICC profiles for images</i> are used for all objects (also for text and line art) and regardless of the chosen (non-image) target profile for "OtherObjects".
TargetOutputIntent OverridesICCProfiles	boolean	optional	If true, the rendering intent overrides the selected ICC profile rendering intent for the target ICC profiles The default value is false

ICCProfiles

This element specifies the source or target ICC Profiles for a particular category of objects.

Each child element specifies the file path to the default ICC Profile for a particular color space. This ICC Profile is used for color converting an object in this color space unless the PDF file explicitly associates an ICC Profile with the object.

If the ICC Profile for a color space is not provided, the corresponding default Enfocus ICC Profile is used instead.

Element name	Type	Multiplicity	Description
Gray	<i>PathType</i>	optional	Path to ICC Profile for Gray color space

Element name	Type	Multiplicity	Description
RGB	<i>PathType</i>	optional	Path to ICC Profile for RGB color space
CMYK	<i>PathType</i>	optional	Path to ICC Profile for CMYK color space
Lab	<i>PathType</i>	optional	Path to ICC Profile for Lab color space

3.6.10. Fonts

This element specifies settings for loading fonts.

Loading fonts can be quite time-consuming. To optimize performance, turn off system fonts if they are not needed, and limit additional fonts to those actually used in the job being processed.

Element name	Type	Multiplicity	Description
UseSystemFonts	boolean	optional	If true (default), the fonts in the system folder are available for handling fonts during processing. If false, the fonts in the system folder are not available.
AdditionalFolder	<i>PathType</i>	zero or more	Path to a folder containing additional fonts that should be available for handling fonts during processing of this task.
FontLicense Restrictions	<i>type_FontLicense</i>	zero or one	Specifies the compliance with font license restrictions.

3.6.10.1. type_FontLicense

This element specifies your compliance with font license restrictions.

Element name	Type	Multiplicity	Description
AgreeWithFont LicenseRestrictions	boolean	required	If present and true, the PitStop Server CLI will assume you comply with the font license restrictions imposed by any font used in the PDF. Note that you must explicitly confirm that you comply with the font license restrictions in the "IComplyWithTheFontLicenseRestrictions" element.
IComplyWithThe FontLicenseRestrictions	boolean	required	Some fonts may be licensed for View and Print only.

Element name	Type	Multiplicity	Description
			By choosing "true", you agree that you have checked the licensing conditions of the print vendor of these fonts and that you are allowed to manipulate these fonts according to this configuration. Enfocus disclaims any liability for any use of the fonts which is not in accordance with the licensing agreement between yourself and the print vendor. Choose "false" if you do not agree.

3.7. ExportImage

This element specifies a request for rendering the contents of a PDF to separate images. There can be multiple ExportImage elements.

Element name	Type	Multiplicity	Description
InputPDF	<i>InputPDF</i>	optional (*)	Location of the input PDF file (*) is in fact required, but for the first Process or ExportImage element may be specified as a command-line option.
OutputImages	<i>OutputImages</i>	optional (*)	Location and settings for the output images (*) is in fact required, but for the first ExportImage element may be specified as a command-line option.
RenderOptions	<i>RenderOptions</i>	optional	The options to be used for rendering the page.
ActionLists	<i>Action Lists</i>	optional	This element specifies the Action Lists to be used before rendering, and to define the selection to be rendered.
SmartPreflight	<i>SmartPreflight</i>	optional	Location of Variable Set and Job Ticket to be used. If no SmartPreflight is defined, image export is executed without Smart Preflighting.
ColorManagement	<i>ColorManagement</i>	optional	Settings for color management

Element name	Type	Multiplicity	Description
Fonts	<i>Fonts</i>	optional	Settings for font management

3.7.1. InputPDF

This element specifies the location of an input PDF file.

Element name	Type	Multiplicity	Description
InputPath	<i>PathType</i>	optional (*)	Path to the input PDF file (*) is in fact required, but for the first Process/ExportImage element may be specified as a command-line option.

3.7.2. OutputImages

This element specifies the location and settings for the output images.

Element name	Type	Multiplicity	Description
OutputPath	<i>PathType</i>	optional (*)	Path for the output rendered images. If multiple images are expected, %1 can be included in the filename (e.g.C:\Temp\Images\image%1.png), which will be used to make the filenames unique. If no %1 is included, the CLI will append a unique number if necessary. (*) is in fact required, but for the first ExportImages element may be specified as a command-line option.
SaveOptions	<i>SaveOptions</i>	optional	Save options for the output images. The attribute "FileType" is required and defines the file type of the output image. Values can be PNG, JPEG or TIFF. If the attribute is used in the first ExportImage element, this value can be overridden with a command line parameter.

3.7.2.1. SaveOptions

This element specifies save options for the rendered images. The available child elements depend on the chosen file type.

<cf:SaveOptions FileType = "PNG">

Element name	Type	Multiplicity	Description
Interlaced	boolean	optional	If present and true, an Adam7 interlaced PNG will be generated.
EmbedICCProfile	boolean	optional	If present and true, the ICC Profile will be embedded in the image file. This option requires that color management is used for images and that RenderType is set to Composite (See RenderOptions on page 37).

<cf:SaveOptions FileType = "JPEG">

Element name	Type	Multiplicity	Description
EmbedICCProfile	boolean	optional	If present and true, the ICC Profile will be embedded in the image file. This option requires that color management is used for images and that RenderType is set to Composite (See RenderOptions on page 37).
Progressive	boolean	optional	If present and true, a progressive JPG will be generated.
CompressionLevel	enumeration	optional	This element specifies the level of compression to be used when saving JPG files. Use one of: • Minimum • Low • Medium (default) • High • Maximum

<cf:SaveOptions FileType = "TIFF">

Element name	Type	Multiplicity	Description
EmbedICCProfile	boolean	optional	If present and true, the ICC Profile will be embedded in the image file. This option requires that color management is used for images and that RenderType is set to

Element name	Type	Multiplicity	Description
			Composite (See RenderOptions on page 37).

3.7.3. RenderOptions

This element specifies the options to be used for rendering the page.

Element name	Type	Multiplicity	Description
RenderType	enumeration	optional	Specifies the way the page is to be rendered: • Composite (default): renders the page as a whole • Separations: renders the various separations as separate images
OutputColorSpace	enumeration	optional	Specifies the output color space to be used: • DeviceGray • DeviceRGB (default) • DeviceCMYK
BackgroundColor	Color	optional	Specifies the background color to be used during rendering. If no background color is specified, the rendered image may contain transparency if the file type supports transparency. If it doesn't, a white background is used. The color space of the background must match the output color space.
RenderArea	enumeration	optional	Specifies which area to be rendered, based on the page box. Values: • MediaBox • CropBox • ArtBox • TrimBox • BleedBox
ImageDimensions	ImageDimensions	optional	Specifies the dimensions of the image to be rendered.

Element name	Type	Multiplicity	Description
IncludeEmptyPages	boolean	optional	Specifies whether or not pages without (selected) content are rendered to images. Values: - False (default): Empty pages and pages that contain no selected content are NOT rendered. - True: Empty pages and pages that contain no selected content are rendered too.
AntiAliasing	boolean	optional	Specifies whether or not images will be rendered with anti-aliasing. Values: - False: rendered with anti-aliasing disabled - True (default): rendered with anti-aliasing enabled

3.7.3.1. ImageDimensions

This element specifies the dimensions of the image to be rendered.

Element name	Type	Multiplicity	Description
Resolution	Floating-point number	optional(*)	The resolution to be used when rendering the page (1 or higher). For decimal numbers, use separator ".". (*) You should either specify resolution or width and height.
Width	Integer	optional(**)	If this element is present, the resulting image will have the specified width in pixels. (**) You can either specify height or width. Alternatively, you can specify both height and width, but in that case, the aspect ratio is not maintained.
Height	Integer	optional(**)	If this element is present, the resulting image will have the specified height in pixels. (**) You can either specify height or width. Alternatively, you can specify both height

Element name	Type	Multiplicity	Description
			and width, but in that case, the aspect ratio is not maintained.

3.7.3.2. Color

This element specifies a color.

Element name	Type	Multiplicity	Description
Gray	Floating-point number	optional	The gray value for grayscale based color. Possible values: • 0 • Any decimal number between 0 and 1, for example 0.2 (use separator ".") • 1 (default)
Red	Integer	optional	The red value for an RGB based color. Possible values: • 0 • Any integer between 0 and 255 • 255 (default)
Green	Integer	optional	The green value for an RGB based color. Possible values: • 0 • Any integer between 0 and 255 • 255 (default)
Blue	Integer	optional	The blue value for an RGB based color. Possible values: • 0 • Any integer between 0 and 255 • 255 (default)
Cyan	Floating-point number	optional	The cyan value for a CMYK based color. Possible values: • 0 (default) • Any decimal number between 0 and 1 (use separator ".") • 1
Magenta	Floating-point number	optional	The magenta value for a CMYK based color. Possible values: • 0 (default)

Element name	Type	Multiplicity	Description
Yellow	Floating-point number	optional	- Any decimal number between 0 and 1 (use separator ".") 1 The yellow value for a CMYK based color. Possible values: 0 (default) - Any decimal number between 0 and 1 (use separator ".") 1
Black	Floating-point number	optional	The black value for a CMYK based color. Possible values: 0 (default) - Any decimal number between 0 and 1 (use separator ".") 1

3.7.4. ActionLists

This element specifies the Action Lists to be used before rendering, and to define the selection to be rendered.

Element name	Type	Multiplicity	Description
PrerenderActionList	PathType	optional	The Action List to be executed before the page is rendered.
RestrictingActionList	PathType	optional	The Action List to select the content that must be rendered. If nothing is selected on a page, the page will not be exported to an image. If no Action List is defined, all visible content is considered selected and will be rendered.

3.7.5. SmartPreflight

This element specifies the settings that should be used for Smart Preflighting the PDF file. One Variable Set and at most one Job Ticket can be specified. Whether or not the contents of the Job Ticket is used is defined by the Variable Set.



Note: For detailed information about Smart Preflight, please refer to the PitStop Server Reference Guide.

Element name	Type	Multiplicity	Description
VariableSet	<i>PathType</i>	required	Path to a Variable Set file
JobTicket	<i>PathType</i>	zero or one	Path to a Job Ticket file

3.7.6. ColorManagement

This element specifies settings related to color management.

Color management can be configured separately for images and all other objects (text, line art), or for all objects (including images) at the same time.

If color management is not turned on for a particular object type, the corresponding source and target ICC profiles are ignored.

Element name	Type	Multiplicity & Description
AllObjects	<i>ColorManagementSettings</i>	Only the following combinations are allowed: - Just “AllObjects”: specify the same color management options for all objects in the file - Both “Images” and “OtherObjects”: specify separate color management options for images and for non-images (text & line-art) - None of these elements: use the default settings for all objects in the file
Images		
OtherObjects	<i>ColorManagementSettings</i>	
UseBlackPoint Compensation	boolean	If present and true, Black Point Compensation will be used. Note that this option is only available if color management is enabled.

3.7.6.1. ColorManagementSettings

This element specifies color management settings for a particular category of objects.

Element name	Type	Multiplicity	Description
Enabled	boolean	optional	If true (default), color management is enabled. If false, the remaining settings in this list are ignored.
RenderingIntent	enumeration	optional	The output rendering intent; one of: ObjectDefined (default): the rendering intent of the object itself,

Element name	Type	Multiplicity	Description
			as shown on the prepress tab of the PitStop Inspector • Relative: in-gamut colors are reproduced exactly; out-of-gamut colors are mapped to the nearest value within the reproducible gamut; corrections are made for the output medium's white point. • Absolute: in-gamut colors are reproduced exactly; out-of-gamut colors are mapped to the nearest value within the reproducible gamut; no correction is made for the output medium's white point. • Saturation: colors are represented in a manner that preserves or emphasizes saturation. • Perceptual: colors are represented in a manner that provides a pleasing perceptual appearance.
SourceICCProfiles	<i>ICCProfiles</i>	optional (*)	The source ICC profiles (*) Required if color management is enabled
SourceOutputIntent OverridesICCProfiles	boolean	optional	If true, the rendering intent overrides the selected ICC profile rendering intent for the source ICC profiles The default value is false
TargetICCProfiles	<i>ICCProfiles</i>	optional	The target ICC profiles. If not provided, the source ICC profiles are used as target ICC profiles as well.  Note: Target ICC profiles set for non-images are only used for pre-rendering. For example, for color conversions (using a pre-render Action List, as the first step of the processing), you can use different profiles for images and other objects. However, to render the PDF to images, the <i>target ICC profiles for images</i> are used for all objects (also for text

Element name	Type	Multiplicity	Description
TargetOutputIntent OverridesICCProfiles	boolean	optional	and line art) and regardless of the chosen (non-image) target profile for "OtherObjects". If true, the rendering intent overrides the selected ICC profile rendering intent for the target ICC profiles The default value is false

ICCProfiles

This element specifies the source or target ICC Profiles for a particular category of objects.

Each child element specifies the file path to the default ICC Profile for a particular color space. This ICC Profile is used for color converting an object in this color space unless the PDF file explicitly associates an ICC Profile with the object.

If the ICC Profile for a color space is not provided, the corresponding default Enfocus ICC Profile is used instead.

Element name	Type	Multiplicity	Description
Gray	<i>PathType</i>	optional	Path to ICC Profile for Gray color space
RGB	<i>PathType</i>	optional	Path to ICC Profile for RGB color space
CMYK	<i>PathType</i>	optional	Path to ICC Profile for CMYK color space
Lab	<i>PathType</i>	optional	Path to ICC Profile for Lab color space

3.7.7. Fonts

This element specifies settings for loading fonts.

Loading fonts can be quite time-consuming. To optimize performance, turn off system fonts if they are not needed, and limit additional fonts to those actually used in the job being processed.

Element name	Type	Multiplicity	Description
UseSystemFonts	boolean	optional	If true (default), the fonts in the system folder are available for handling fonts during processing. If false, the fonts in the system folder are not available.

Element name	Type	Multiplicity	Description
AdditionalFolder	<i>PathType</i>	zero or more	Path to a folder containing additional fonts that should be available for handling fonts during processing of this task.
FontLicense Restrictions	<i>type_FontLicense</i>	zero or one	Specifies the compliance with font license restrictions.

3.7.7.1. type_FontLicense

This element specifies your compliance with font license restrictions.

Element name	Type	Multiplicity	Description
AgreeWithFont LicenseRestrictions	boolean	required	If present and true, the PitStop Server CLI will assume you comply with the font license restrictions imposed by any font used in the PDF. Note that you must explicitly confirm that you comply with the font license restrictions in the "IComplyWithTheFontLicenseRestrictions" element.
IComplyWithThe FontLicenseRestrictions	boolean	required	Some fonts may be licensed for View and Print only. By choosing "true", you agree that you have checked the licensing conditions of the print vendor of these fonts and that you are allowed to manipulate these fonts according to this configuration. Enfocus disclaims any liability for any use of the fonts which is not in accordance with the licensing agreement between yourself and the print vendor. Choose "false" if you do not agree.

4. Task Report XML file

4.1. Introduction

When a task report path is specified on the command line or in the configuration file, PitStop Server CLI creates a task report. By default the task report contains only minimal status information. However the configuration file can request additional information to be included in the task report (See [Configuration XML file](#) on page 14). Examples include:

- The errors and warnings produced by a preflight operation.
- Information about the exported images resulting from an ExportImage task.
- A list of available Preflight Profiles.
- Debugging information on the CLI's execution.

The task report is constructed as a tree of XML elements. The remaining sections in this chapter describe each element that may appear in the file and its immediate child elements.

4.1.1. Unicode support

The task report is a well-formed XML document using UTF-8 encoding, which means that it fully supports Unicode for text values such as file names.

4.1.2. XML namespace and schema

XML namespace	http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_TaskReport.xsd
Preferred prefix	tr (or use default namespace)
Schema definition	PitStopServerCLI_TaskReport.xsd

The task report generated by PitStopServerCLI uses the default namespace but it also defines the “tr” prefix to facilitate querying the report with xslt in Switch.

4.1.3. PathType

This is a string type representing an absolute file or folder path in the native platform format, for example:

- On Windows: C:\Preflight\Input\input.pdf
- On Mac: /Volumes/Preflight/Input/input.pdf

4.2. TaskReport

This is the root element of the task report file. Its child elements are generated in a logical execution order, not necessarily in the order presented in the following table.

Element name	Type	Multiplicity	Description
FormatVersion	integer	required	The format version of this task report. Currently this is “3”.
ExitCode	integer	required	The exit code returned by the CLI. This is always present, assuming that the task report could be created.
ErrorCode	integer	optional	If the exit code is nonzero, the error code as written to stdout (assuming that the task report could be created).
ErrorMessage	string	optional	If the exit code is nonzero, the error message as written to stdout, without the leading error code and colon (assuming that the task report could be created).
VersionInfo	VersionInfo	optional (if requested)	Version information on the PitStop Server CLI generating this task report.
LibraryVersionInfo	VersionInfo	optional (if requested)	Version information on the PitStop Library used by the PitStop Server CLI generating this task report.
SupportInfo	SupportInfo	optional (if requested)	Information useful for support and debugging purposes.
CommandLine	CommandLine	optional (if requested)	A list of the options received (and recognized) on the command line.
ProcessResults	ProcessResults	zero or more (if requested)	The number of errors, warnings, fixes, signoffs, failures and critical failures for each Process task.
ImageExportResults	ImageExportResults	zero or more (if requested)	Information on the results of an ImageExport task.

Element name	Type	Multiplicity	Description
Errors	<i>Errors</i>	optional	A list of error and warning messages encountered during execution.
Languages	<i>Languages</i>	optional (if requested)	A list of the languages supported by PitStop Server CLI.
DefaultProfileDB	<i>MutatorDB</i>	optional (if requested)	A list of the Preflight Profiles in the default database.
LocalProfileDB	<i>MutatorDB</i>	optional (if requested)	A list of the Preflight Profiles in the local database.
DefaultActionDB	<i>MutatorDB</i>	optional (if requested)	A list of the Action Lists in the default database.
LocalActionDB	<i>MutatorDB</i>	optional (if requested)	A list of the Action Lists in the local database.
MutatorInfo	<i>MutatorInfo</i>	zero or more (as requested)	Information on a mutator, i.e. a Preflight Profile or an Action List.

4.2.1. VersionInfo

This element offers version information on the CLI (VersionInfo) or on the associated PitStop Library (LibraryVersionInfo).

Element name	Type	Multiplicity	Description
DisplayVersion	string	required	The version string as it would be displayed to a user, for example "24.03".
Major	integer	required	The major version number, e.g. "24".
Minor	integer	required	The minor version number, e.g. "3".
BuildType	enumeration	required	The build type; one of: - Alpha - Beta - ReleaseCandidate - PreRelease - Final

Element name	Type	Multiplicity	Description
ReleaseNumber	integer	optional	The release number; this is not present for final builds.
BuildNumber	integer	required	The internal build sequence number.

4.2.2. SupportInfo

This element offers information that is useful for Enfocus technical support. Its content is not documented and may be changed without notice in future versions of the task report.

4.2.3. CommandLine

This element lists the values of the command line options as they were recognized by PitStop Server CLI after merging with the corresponding values in the first Process or ExportImage element and the TaskReport element in the configuration file.

A child element is not listed if both the command line option and the corresponding value in the configuration file are missing.

Element name	Type	Multiplicity	Description
Config	<i>PathType</i>	optional	Absolute path to the configuration file
Input	<i>PathType</i>	optional	Absolute path to the PDF input file
Mutator	<i>PathType</i>	zero or more	Absolute path to the mutators used for processing
Output	<i>PathType</i>	optional	Absolute path to the PDF output file or output images
ReportPDF	<i>PathType</i>	optional	Absolute path to the PDF Report file
ReportPDFTpl	<i>PathType</i>	optional	Absolute path to the PDF Report template file
ReportXML	<i>PathType</i>	optional	Absolute path to the XML Report file
ReportJSON	<i>PathType</i>	optional	Absolute path to the JSON Report file
TaskReport	<i>PathType</i>	required	Absolute path to the task Report file

4.2.4. ProcessResults

This element offers information on the results of a process task. A separate ProcessResults element is provided for each Process element in the configuration file.

Element name	Type	Multiplicity	Description
Errors	integer	required	Number of errors reported during processing
Warnings	integer	required	Number of warnings reported during processing
Fixes	integer	required	Number of fixes reported during processing
Signoffs	integer	required	Number of sign-offs reported during processing
Failures	integer	required	Number of failures reported during processing
NonCriticalFailures	integer	required	Number of non-critical failures reported during processing

4.2.5. ImageExportResults

This element offers information on the results of an ExportImage task. A separate ImageExportResults element is provided for each ExportImage element in the configuration file. The ImageExportResults element can have a TaskID attribute, specifying the ExportImage task which generated these results.



Note: If the ExportImage task did not result in any exported images, it will not contain any elements.

Element name	Type	Multiplicity	Description
Image	<i>PathType</i>	Optional	Information about each exported image. Attributes: • Page: This attribute contains the zero based page number from which the image was rendered. • Separation: If the image was rendered using Separations as RenderType, this attribute will contain the name of the separation (See RenderOptions on page 37).

4.2.6. Errors

This element lists any error and warning messages encountered during execution. There is only a single “Errors” element, i.e. errors are not split per process or task.

Element name	Type	Multiplicity	Description
Error	<i>Error</i>	zero or more	Information about an error or warning message

4.2.6.1. Error

This element offers information about an error or warning message

Element name	Type	Multiplicity	Description
TimeStamp	date-time	required	The date and time the error or warning occurred.
Message	string	required	A message describing the error or warning in English.
ErrorCode	integer	optional	An error code corresponding to the error or warning, if available.
Severity	integer	optional	An indication of the severity of this error or warning; higher numbers indicate more severe errors. The default value is zero, which should be used for warnings.

4.2.7. Languages

This element lists the Preflight Report languages supported by PitStop Server CLI.

Element name	Type	Multiplicity	Description
Language	enumeration	one or more	One of the supported languages, represented by their translated name. The attribute is a 4-character string in the form 'enUS','frFR', 'deDE',... English is always available.

4.2.8. MutatorDB

These elements (DefaultProfileDB, LocalProfileDB, DefaultActionDB, LocalActionDB) list the mutators in one of the predefined databases plus any requested information on these mutators.

Element name	Type	Multiplicity	Description
MutatorInfo	<i>MutatorInfo</i>	zero or more	Information on one of the mutators in the predefined database

4.2.9. MutatorInfo

This element lists information about a mutator. It can occur in two places:

- As a child of one of the MutatorDB elements.
- As a standalone child of the TaskReport, in response to a QueryMutatorInfo request.

Element name	Type	Multiplicity	Description
MutatorPath	<i>PathType</i>	required	The absolute file path to the mutator (Preflight Profile or Action List).
Name	string	optional	The name of the mutator.
Company	string	optional	The company of the author of the mutator.
Author	string	optional	The author of the mutator.
Description	string	optional	The description of the mutator.
MutatorType	enumeration	optional	The mutator type: PreflightProfile or ActionList.
DateTime	date-time	optional	The most recent modification date and time of the mutator.
Version	integer	optional	The version of the mutator.
IsFullyUnderstood	boolean	optional	True if PitStop Server CLI fully supports all settings and instructions in this mutator.
IsVersionCorrect	boolean	optional	True if the version of the mutator is correct.
IsConfigurationCorrect	boolean	optional	True if the configuration of the mutator is correct.
IsUsableAsRestriction	boolean	optional	True if the mutator can be used as a restricting Action List.

5. Task identifiers

5.1. Introduction

5.1.1. Logical order

Information in the task report is generally listed in a logical order. For example:

- ProcessResults elements in the task report are listed in the same order as the corresponding Process elements in the configuration file.
- MutatorInfo elements in the task report are listed in the same order as the corresponding QueryMutatorInfo elements in the configuration file.

Still it is not trivial to locate the information associated with a particular task or query.

5.1.2. Task identifiers

Task identifiers help locate information in the task report as follows:

- Selected elements in the configuration file allow an XML attribute called “TaskID” which can have an arbitrary string value.
- If a TaskID attribute is specified in the configuration file, the corresponding elements in the task report also have a TaskID attribute with the same value.

Thus one can locate information in the task report simply by locating elements with the appropriate value for the TaskID attribute.

5.1.3. XML namespace

The TaskID attribute has no namespace prefix.

5.1.4. Empty value

Specifying an empty TaskID attribute value is equivalent to specifying no TaskID attribute, and vice versa.

5.2. Supported elements

The following table presents the list of elements in the configuration file supporting the TaskID attribute, and the corresponding elements in the task report that “inherit” the value of the TaskID attribute.

Configuration elements supporting TaskID	Task report elements inheriting TaskID
Initialize	Error
Process	ProcessResults, Error
ExportImage	ImageExportResults
QueryMutatorInfo	MutatorInfo, Error

Specifying a TaskID attribute on any other element has no effect.

6. Appendix

6.1. Example Configurations

6.1.1. Flattening a PDF

```
<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

  <cf:Versioning>
    <cf:Version>15</cf:Version>
    <cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
  </cf:Versioning>

  <cf:Initialize>
    <cf:ProcessingMethod>EnforceServer</cf:ProcessingMethod> <!-- This is the fastest
way -->
  </cf:Initialize>

  <!-- This flattens a PDF -->
  <cf:Process>
    <cf:InputPDF>
      <cf:InputPath>D:\Flattening\Input.pdf</cf:InputPath> <!-- This path can also be
passed through command line -->
    </cf:InputPDF>
    <cf:OutputPDF>
      <cf:OutputPath>D:\Flattening\Output.pdf</cf:OutputPath> <!-- This path can also be
passed through command line -->
    </cf:OutputPDF>
    <cf:Flattening>
      <cf:RasterVectorBalance>75</cf:RasterVectorBalance>
      <cf:VectorResolution>300</cf:VectorResolution>
      <cf:GradientResolution>150</cf:GradientResolution>
    </cf:Flattening>
    <cf:CertifiedPDF>
      <cf:CertifiedPDFAction>KeepStatusUnchanged</cf:CertifiedPDFAction> <!-- Making
it certified is a good default if you're preflighting, but less so if you're only
flattening -->
    </cf:CertifiedPDF>
  </cf:Process>

</cf:Configuration>
```

6.1.2. Retrieving Preflight Profile information

```
<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

  <cf:Versioning>
    <cf:Version>15</cf:Version>
    <cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
  </cf:Versioning>

  <!-- This writes the information about a preflight profile to an XML file -->
  <cf:TaskReport>
```

```

<cf:TaskReportPath>D:\Info\TaskReport.xml</cf:TaskReportPath> <!-- This path can
also be passed through command line -->
<cf:QueryMutatorInfo>
  <cf:MutatorPath>C:\Program Files\Enfocus\PitStop Server 24\Resources\PDF
Profiles\Ghent PDF Workgroup\2012 Specifications (PDFX-4)\GWG_MagazineAds_2012.ppp</
cf:MutatorPath>
  <cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>Company</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>Author</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>Description</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>MutatorType</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>IsFullyUnderstood</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>IsVersionCorrect</cf:MutatorInfoOptions>
  <cf:MutatorInfoOptions>IsConfigurationCorrect</cf:MutatorInfoOptions>
</cf:QueryMutatorInfo>
</cf:TaskReport>

</cf:Configuration>

```

6.1.3. Converting a PDF to images

```

<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

  <cf:Versioning>
    <cf:Version>15</cf:Version>
    <cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
  </cf:Versioning>

  <cf:Initialize>
    <cf:ProcessingMethod>EnforceInternal</cf:ProcessingMethod> <!-- PDF 2 image cannot
be off loaded -->
  </cf:Initialize>

  <cf:TaskReport>
    <cf:TaskReportPath>D:\PDF2Image\TaskReport.xml</cf:TaskReportPath> <!-- This path
can also be passed through command line -->
    <cf:LogExportImageResults>true</cf:LogExportImageResults>
  </cf:TaskReport>

  <cf:ExportImage TaskID="My Render Job">
    <cf:InputPDF>
      <cf:InputPath>D:\PDF2Image\Input.pdf</cf:InputPath> <!-- This path can also be
passed through command line -->
    </cf:InputPDF>
    <cf:OutputImages>
      <cf:OutputPath>D:\PDF2Image\Output_%1.png</cf:OutputPath> <!-- This path can also
be passed through command line -->
      <cf:SaveOptions FileType="PNG">
        <cf:Interlaced>true</cf:Interlaced>
      </cf:SaveOptions>
    </cf:OutputImages>
    <cf:RenderOptions>
      <cf:RenderType>Separations</cf:RenderType>
      <cf:BackgroundColor>
        <cf:Red>255</cf:Red>
        <cf:Green>255</cf:Green>
        <cf:Blue>255</cf:Blue>
      </cf:BackgroundColor>
      <cf:RenderArea>BleedBox</cf:RenderArea>
      <cf:ImageDimensions>
        <cf:Width>600</cf:Width>
      </cf:ImageDimensions>
      <cf:IncludeEmptyPages>true</cf:IncludeEmptyPages>
      <cf:AntiAliasing>false</cf:AntiAliasing>
    </cf:RenderOptions>
  </cf:ExportImage>

```

```
</cf:Configuration>
```

6.1.4. Validating a PDF against a GWG Profile

```
<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

  <cf:Versioning>
    <cf:Version>15</cf:Version>
    <cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
  </cf:Versioning>

  <cf:Initialize>
    <cf:ProcessingMethod>EnforceServer</cf:ProcessingMethod> <!-- This is the fastest
option -->
  </cf:Initialize>

  <cf:Process>
    <cf:InputPDF>
      <cf:InputPath>D:\Processing\Input.pdf</cf:InputPath> <!-- This path can also be
passed through command line -->
    </cf:InputPDF>
    <cf:OutputPDF>
      <cf:OutputPath>D:\Processing\Output.pdf</cf:OutputPath> <!-- This path can also be
passed through command line -->
    </cf:OutputPDF>
    <cf:Reports>
      <cf:ReportPDF>
        <cf:ReportPath>D:\Processing\Report.pdf</cf:ReportPath> <!-- This path can also be
passed through the command line -->
      </cf:ReportPDF>
    </cf:Reports>
    <cf:Mutators>
      <cf:PreflightProfile>C:\Program Files\Enfocus\Enfocus PitStop Server
24\Resources\PDF Profiles\Ghent PDF Workgroup\2012 Specifications
(PDFX-4)\GWG_MagazineAds_2012.ppp</cf:PreflightProfile>
    </cf:Mutators>
    <cf:CertifiedPDF>
      <cf:CertifiedPDFAction>MakeCertified</cf:CertifiedPDFAction>
      <cf:UserInfo>
        <cf:Name>Jane Doe</cf:Name>
        <cf:Company>Enfocus, an Esko Company</cf:Company>
        <cf:Street>Raymonde de Larochelaan 13</cf:Street>
        <cf:City>Ghent</cf:City>
        <cf:Country>Belgium</cf:Country>
        <cf:PostalCode>9051</cf:PostalCode>
        <cf:Email>jane.doe@enfocus.com</cf:Email>
      </cf:UserInfo>
      <cf:SessionComment>Making the file comply with GWG 2012</cf:SessionComment>
    </cf:CertifiedPDF>
    <cf:Language>frFR</cf:Language>
    <cf:MeasurementUnit>Millimeter</cf:MeasurementUnit>
  </cf:Process>

</cf:Configuration>
```

6.1.5. Processing image input

```
<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

  <cf:Versioning>
    <cf:Version>15</cf:Version>
    <cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
  </cf:Versioning>
```

```

<cf:Initialize>
  <cf:ProcessingMethod>EnforceServer</cf:ProcessingMethod>
</cf:Initialize>

<cf:Process>
  <cf:InputImage>
    <cf:InputPath>/Data/Preflight/Input/inputimage.png</cf:InputPath>
    <cf:PageSize>
      <cf:Width>595</cf:Width>
      <!-- The height will be kept proportional to the width. -->
    </cf:PageSize>
    <cf:PageSizeOverridesImageMetadata>false</cf:PageSizeOverridesImageMetadata> <!--
The embedded image metadata, if present, will override the given width. -->
  </cf:InputImage>
  <cf:OutputPDF>
    <cf:OutputPath>/Data/Preflight/Output/output.pdf</cf:OutputPath>
  </cf:OutputPDF>
  <cf:Reports>
    <cf:ReportPDF>
      <cf:ReportPath>/Data/Preflight/Output/report.pdf</cf:ReportPath>
    </cf:ReportPDF>
  </cf:Reports>
  <cf:Mutators>
    <cf:ActionList>/Applications/Enfocus/Enfocus PitStop Server 24/Resources/Action
Lists/Add/Add my Printer Marks and Enlarge.eal</cf:ActionList>
  </cf:Mutators>
  <cf:CertifiedPDF>
    <cf:CertifiedPDFAction>MakeUncertified</cf:CertifiedPDFAction>
  </cf:CertifiedPDF>
</cf:Process>

</cf:Configuration>

```

6.1.6. Full Configuration (Windows)

```

<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

  <cf:Versioning>
    <cf:Version>15</cf:Version>
    <cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
  </cf:Versioning>

  <cf:Initialize>
    <cf:TempPath>C:\temp</cf:TempPath>
    <cf:ProcessingMethod>EnforceServer</cf:ProcessingMethod>
    <cf:ShutDownServerAtExit>true</cf:ShutDownServerAtExit>
  </cf:Initialize>

  <cf:TaskReport>
    <cf:TaskReportPath>C:\Users\user\Desktop\MyTestTaskReport.xml</cf:TaskReportPath>
    <cf:LogVersionInfo>true</cf:LogVersionInfo>
    <cf:LogSupportInfo>true</cf:LogSupportInfo>
    <cf:LogCommandLine>true</cf:LogCommandLine>
    <cf:LogProcessResults>true</cf:LogProcessResults>
    <cf:LogExportImageResults>true</cf:LogExportImageResults>
    <cf:LogErrors>true</cf:LogErrors>
    <cf:QueryLanguages>true</cf:QueryLanguages>
    <cf:QueryCMMs>true</cf:QueryCMMs>
    <cf:QueryDefaultProfileDB>
      <cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
      <cf:MutatorInfoOptions>Company</cf:MutatorInfoOptions>
    </cf:QueryDefaultProfileDB>
    <cf:QueryLocalProfileDB>
      <cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
    </cf:QueryLocalProfileDB>
    <cf:QueryDefaultActionDB>
      <cf:MutatorInfoOptions>IsVersionCorrect</cf:MutatorInfoOptions>
    </cf:QueryDefaultActionDB>
    <cf:QueryLocalActionDB>

```

```

    <cf:MutatorInfoOptions>DateTime</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsUsableAsRestriction</cf:MutatorInfoOptions>
  </cf:QueryLocalActionDB>
  <cf:QueryMutatorInfo>
    <cf:MutatorPath>C:\Users\user\Desktop\My Action List Collection\Add Banner.eal</
cf:MutatorPath>
    <cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Version</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsConfigurationCorrect</cf:MutatorInfoOptions>
  </cf:QueryMutatorInfo>
  <cf:QueryMutatorInfo TaskID="My Preflight Profile">
    <cf:MutatorPath>C:\Users\user\Desktop\My Preflight Profile Collection\Custom.ppp</
cf:MutatorPath>
    <cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Company</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Author</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Description</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>MutatorType</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>DateTime</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Version</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsFullyUnderstood</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsVersionCorrect</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsConfigurationCorrect</cf:MutatorInfoOptions>
  </cf:QueryMutatorInfo>
</cf:TaskReport>

<cf:Process TaskID="My Process Job">
  <cf:InputPDF>
    <cf:InputPath>C:\Users\user\Desktop\Temp\Input.pdf</cf:InputPath>
  </cf:InputPDF>
  <cf:OutputPDF>
    <cf:OutputPath>C:\Users\user\Desktop\Temp\Output.pdf</cf:OutputPath>
    <cf:SaveOptions>
      <cf:PerformFullSave>true</cf:PerformFullSave>
      <cf:Optimization>Disabled</cf:Optimization>
    </cf:SaveOptions>
  </cf:OutputPDF>
  <cf:Reports>
    <cf:ReportPDF>
      <cf:ReportPath>C:\Users\user\Desktop\Temp\Report.pdf</cf:ReportPath>
      <cf:ReportTemplatePath>C:\Users\user\Desktop\Gears\PitStopReportGears.prefs</
cf:ReportTemplatePath>
    </cf:ReportPDF>
    <cf:ReportXML>
      <cf:ReportPath>C:\Users\user\Desktop\Temp\Report.xml</cf:ReportPath>
      <cf:Version>3</cf:Version>
      <cf:MaxReportedNbItemsPerCategory>50</cf:MaxReportedNbItemsPerCategory>
      <cf:MaxReportedNbOccurrencesPerItem>75</cf:MaxReportedNbOccurrencesPerItem>
    </cf:ReportXML>
    <cf:ReportJSON>
      <cf:ReportPath>C:\Users\user\Desktop\Temp\Report.json</cf:ReportPath>
      <cf:MaxReportedNbItemsPerCategory>50</cf:MaxReportedNbItemsPerCategory>
      <cf:MaxReportedNbOccurrencesPerItem>75</cf:MaxReportedNbOccurrencesPerItem>
    </cf:ReportJSON>
  </cf:Reports>
  <cf:Flattening>
    <cf:RasterVectorBalance>75</cf:RasterVectorBalance>
    <cf:VectorResolution>300</cf:VectorResolution>
    <cf:GradientResolution>150</cf:GradientResolution>
    <cf:ConvertAllText>false</cf:ConvertAllText>
    <cf:ConvertAllStrokes>true</cf:ConvertAllStrokes>
    <cf:ClipComplexRegions>true</cf:ClipComplexRegions>
    <cf:PreserveOverprint>true</cf:PreserveOverprint>
    <cf:BlendingColorSpace Type="ICCProfile">C:\Windows\System32\spool\drivers\color
\UncoatedFOGRA29.icc</cf:BlendingColorSpace>
    <cf:RemoveICCProfiles>true</cf:RemoveICCProfiles>
    <cf:ImageRecompression>
      <cf:Color>JPEGMedium</cf:Color>
      <cf:Grayscale>ZIP8bit</cf:Grayscale>
      <cf:OneBit>RunLength</cf:OneBit>
      <cf:ASCIIFilter>ASCIIFilter</cf:ASCIIFilter>
    </cf:ImageRecompression>
  </cf:Flattening>
  <cf:Mutators>
    <cf>ActionList>C:\Users\user\Desktop\My Action List Collection\Add Stamp.eal</
cf>ActionList>

```

```
<cf:ActionList>C:\Users\user\Desktop\My Action List Collection\Rotate.eal</cf:ActionList>
<cf:PreflightProfile>C:\Users\user\Desktop\My Preflight Profile Collection\Modified MagazineAds_lv3.ppp</cf:PreflightProfile>
</cf:Mutators>
<cf:SmartPreflight>
  <cf:VariableSet>C:\Users\user\Desktop\My Action Variable Set Collection\Page Size.evs</cf:VariableSet>
  <cf:JobTicket>C:\Users\user\Desktop\Temp\JobTicket.xml</cf:JobTicket>
</cf:SmartPreflight>
<cf:CertifiedPDF>
  <cf:CertifiedPDFAction>MakeCertified</cf:CertifiedPDFAction>
  <cf:KeepOriginalProfile>false</cf:KeepOriginalProfile>
  <cf:UserInfo>
    <cf:Name>Name</cf:Name>
    <cf:Company>Company</cf:Company>
    <cf:Street>Street</cf:Street>
    <cf:City>City</cf:City>
    <cf:State>State</cf:State>
    <cf:Country>Country</cf:Country>
    <cf:PostalCode>PostalCode</cf:PostalCode>
    <cf:Phone>Phone</cf:Phone>
    <cf:Fax>Fax</cf:Fax>
    <cf:Email>Email</cf:Email>
    <cf:Message>Message</cf:Message>
  </cf:UserInfo>
  <cf:SessionComment>SessionComment</cf:SessionComment>
</cf:CertifiedPDF>
<cf:ColorManagement>
  <cf:Images>
    <cf:Enabled>true</cf:Enabled>
    <cf:RenderingIntent>ObjectDefined</cf:RenderingIntent>
    <cf:SourceICCProfiles>
      <cf:Gray>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic Enfocus Gray.icm</cf:Gray>
      <cf:RGB>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC \AdobeRGB1998.icc</cf:RGB>
      <cf:CMYK>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\WAN-IFRA\ISOcoated_v2_eci.icc</cf:CMYK>
      <cf:Lab>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic Enfocus Lab.icm</cf:Lab>
    </cf:SourceICCProfiles>
    <cf:SourceOutputIntentOverridesICCProfiles>
      false
    </cf:SourceOutputIntentOverridesICCProfiles>
    <cf:TargetICCProfiles>
      <cf:Gray>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic Enfocus Gray.icm</cf:Gray>
      <cf:RGB>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC \AdobeRGB1998.icc</cf:RGB>
      <cf:CMYK>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\WAN-IFRA\ISOcoated_v2_eci.icc</cf:CMYK>
      <cf:Lab>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic Enfocus Lab.icm</cf:Lab>
    </cf:TargetICCProfiles>
    <cf:TargetOutputIntentOverridesICCProfiles>
      false
    </cf:TargetOutputIntentOverridesICCProfiles>
  </cf:Images>
  <cf:OtherObjects>
    <cf:Enabled>true</cf:Enabled>
    <cf:RenderingIntent>ObjectDefined</cf:RenderingIntent>
    <cf:SourceICCProfiles>
      <cf:Gray>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic Enfocus Gray.icm</cf:Gray>
      <cf:RGB>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC \AdobeRGB1998.icc</cf:RGB>
      <cf:CMYK>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\WAN-IFRA\ISOcoated_v2_eci.icc</cf:CMYK>
      <cf:Lab>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic Enfocus Lab.icm</cf:Lab>
    </cf:SourceICCProfiles>
    <cf:SourceOutputIntentOverridesICCProfiles>
      false
    </cf:SourceOutputIntentOverridesICCProfiles>
    <cf:TargetICCProfiles>
```

```

    <cf:Gray>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic
    Enfocus Gray.icm</cf:Gray>
    <cf:RGB>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC
    \AdobeRGB1998.icc</cf:RGB>
    <cf:CMYK>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\WAN-
    IFRA\ISOcoated_v2_eci.icc</cf:CMYK>
    <cf:Lab>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic
    Enfocus Lab.icm</cf:Lab>
    </cf:TargetICCProfiles>
    <cf:TargetOutputIntentOverridesICCProfiles>
    false
    </cf:TargetOutputIntentOverridesICCProfiles>
    </cf:OtherObjects>
    <cf:UseBlackPointCompensation>true</cf:UseBlackPointCompensation>
    </cf:ColorManagement>
    <cf:Fonts>
    <cf:UseSystemFonts>true</cf:UseSystemFonts>
    <cf:AdditionalFolder>C:\Users\user\Desktop\Collected Fonts</cf:AdditionalFolder>
    </cf:Fonts>
    <cf:Language>enUS</cf:Language>
    <cf:MeasurementUnit>Point</cf:MeasurementUnit>
    </cf:Process>

    <cf:ExportImage TaskID="My Render Job">
    <cf:InputPDF>
    <cf:InputPath>C:\Users\user\Desktop\Temp\Input.pdf</cf:InputPath>
    </cf:InputPDF>
    <cf:OutputImages>
    <cf:OutputPath>C:\Users\user\Desktop\Temp\Images\image%1.png</cf:OutputPath>
    <cf:SaveOptions FileType="PNG">
    <cf:Interlaced>true</cf:Interlaced>
    <cf:EmbedICCProfile>true</cf:EmbedICCProfile>
    </cf:SaveOptions>
    </cf:OutputImages>
    <cf:RenderOptions>
    <cf:RenderType>Separations</cf:RenderType>
    <cf:OutputColorSpace>DeviceGray</cf:OutputColorSpace>
    <cf:BackgroundColor>
    <cf:Gray>0.2</cf:Gray>
    </cf:BackgroundColor>
    <cf:RenderArea>BleedBox</cf:RenderArea>
    <cf:ImageDimensions>
    <cf:Width>600</cf:Width>
    </cf:ImageDimensions>
    <cf:IncludeEmptyPages>true</cf:IncludeEmptyPages>
    <cf:AntiAliasing>false</cf:AntiAliasing>
    </cf:RenderOptions>
    <cf>ActionLists>
    <cf:PrerenderActionList>C:\Users\user\Desktop\My Action List Collection\Add
    Watermark.eal</cf:PrerenderActionList>
    <cf:RestrictingActionList>C:\Users\user\Desktop\My Action List Collection\Select
    Artwork And Language Layer.eal</cf:RestrictingActionList>
    </cf>ActionLists>
    <cf:SmartPreflight>
    <cf:VariableSet>C:\Users\user\Desktop\My Action Variable Set Collection\Language
    Selection.evs</cf:VariableSet>
    <cf:JobTicket>C:\Users\user\Desktop\Temp\JobTicket.xml</cf:JobTicket>
    </cf:SmartPreflight>
    <cf:ColorManagement>
    <cf:AllObjects>
    <cf:Enabled>true</cf:Enabled>
    <cf:RenderingIntent>ObjectDefined</cf:RenderingIntent>
    <cf:SourceICCProfiles>
    <cf:Gray>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic
    Enfocus Gray.icm</cf:Gray>
    <cf:RGB>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC
    \AdobeRGB1998.icc</cf:RGB>
    <cf:CMYK>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\WAN-
    IFRA\ISOcoated_v2_eci.icc</cf:CMYK>
    <cf:Lab>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic
    Enfocus Lab.icm</cf:Lab>
    </cf:SourceICCProfiles>
    <cf:SourceOutputIntentOverridesICCProfiles>
    false
    </cf:SourceOutputIntentOverridesICCProfiles>
    <cf:TargetICCProfiles>

```

```
<cf:Gray>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic
Enfocus Gray.icm</cf:Gray>
<cf:RGB>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC
\AdobeRGB1998.icc</cf:RGB>
<cf:CMYK>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\WAN-
IFRA\ISOcoated_v2_eci.icc</cf:CMYK>
<cf:Lab>C:\Program Files\Enfocus\Enfocus PitStop Server 24\Resources\ICC\Generic
Enfocus Lab.icm</cf:Lab>
</cf:TargetICCProfiles>
<cf:TargetOutputIntentOverridesICCProfiles>
false
</cf:TargetOutputIntentOverridesICCProfiles>
</cf:AllObjects>
<cf:UseBlackPointCompensation>true</cf:UseBlackPointCompensation>
</cf:ColorManagement>
<cf:Fonts>
<cf:UseSystemFonts>true</cf:UseSystemFonts>
<cf:AdditionalFolder>C:\Users\user\Desktop\Collected Fonts</cf:AdditionalFolder>
</cf:Fonts>
</cf:ExportImage>
</cf:Configuration>
```

6.1.7. Full Configuration (Mac)

```
<?xml version="1.0" encoding="utf-8"?>
<cf:Configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:cf="http://www.enfocus.com/PitStop/24.11/PitStopServerCLI_Configuration.xsd">

<cf:Versioning>
<cf:Version>15</cf:Version>
<cf:VersioningStrategy>BestEffort</cf:VersioningStrategy>
</cf:Versioning>

<cf:Initialize>
<cf:TempPath>/Volumes/Temp</cf:TempPath>
<cf:ProcessingMethod>EnforceServer</cf:ProcessingMethod>
<cf:ShutDownServerAtExit>true</cf:ShutDownServerAtExit>
</cf:Initialize>

<cf:TaskReport>
<cf:TaskReportPath>/Users/user/Desktop/MyTestTaskReport.xml</cf:TaskReportPath>
<cf:LogVersionInfo>true</cf:LogVersionInfo>
<cf:LogSupportInfo>true</cf:LogSupportInfo>
<cf:LogCommandLine>true</cf:LogCommandLine>
<cf:LogProcessResults>true</cf:LogProcessResults>
<cf:LogExportImageResults>true</cf:LogExportImageResults>
<cf:LogErrors>true</cf:LogErrors>
<cf:QueryLanguages>true</cf:QueryLanguages>
<cf:QueryCMMs>true</cf:QueryCMMs>
<cf:QueryDefaultProfileDB>
<cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
<cf:MutatorInfoOptions>Company</cf:MutatorInfoOptions>
</cf:QueryDefaultProfileDB>
<cf:QueryLocalProfileDB>
<cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
</cf:QueryLocalProfileDB>
<cf:QueryDefaultActionDB>
<cf:MutatorInfoOptions>IsVersionCorrect</cf:MutatorInfoOptions>
</cf:QueryDefaultActionDB>
<cf:QueryLocalActionDB>
<cf:MutatorInfoOptions>DateTime</cf:MutatorInfoOptions>
<cf:MutatorInfoOptions>IsUsableAsRestriction</cf:MutatorInfoOptions>
</cf:QueryLocalActionDB>
<cf:QueryMutatorInfo>
<cf:MutatorPath>/Users/user/Desktop/My Action List Collection/Add Banner.eal</
cf:MutatorPath>
<cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
<cf:MutatorInfoOptions>Version</cf:MutatorInfoOptions>
<cf:MutatorInfoOptions>IsConfigurationCorrect</cf:MutatorInfoOptions>
</cf:QueryMutatorInfo>
<cf:QueryMutatorInfo TaskID="My Preflight Profile">
```

```

    <cf:MutatorPath>/Users/user/Desktop/My Preflight Profile Collection/Custom.ppp</cf:MutatorPath>
    <cf:MutatorInfoOptions>Name</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Company</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Author</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Description</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>MutatorType</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>DateTime</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>Version</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsFullyUnderstood</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsVersionCorrect</cf:MutatorInfoOptions>
    <cf:MutatorInfoOptions>IsConfigurationCorrect</cf:MutatorInfoOptions>
  </cf:QueryMutatorInfo>
</cf:TaskReport>

<cf:Process TaskID="My Process Job">
  <cf:InputPDF>
    <cf:InputPath>/Users/user/Desktop/Temp/Input.pdf</cf:InputPath>
  </cf:InputPDF>
  <cf:OutputPDF>
    <cf:OutputPath>/Users/user/Desktop/Temp/Output.pdf</cf:OutputPath>
    <cf:SaveOptions>
      <cf:PerformFullSave>true</cf:PerformFullSave>
      <cf:Optimization>Disabled</cf:Optimization>
    </cf:SaveOptions>
  </cf:OutputPDF>
  <cf:Reports>
    <cf:ReportPDF>
      <cf:ReportPath>/Users/user/Desktop/Temp/Report.pdf</cf:ReportPath>
      <cf:ReportTemplatePath>/Library/Preferences/Enfocus Prefs Folder/Report Templates/Custom/Gears/PitStopReportGears.prefs</cf:ReportTemplatePath>
    </cf:ReportPDF>
    <cf:ReportXML>
      <cf:ReportPath>/Users/user/Desktop/Temp/Report.xml</cf:ReportPath>
      <cf:Version>3</cf:Version>
      <cf:MaxReportedNbItemsPerCategory>50</cf:MaxReportedNbItemsPerCategory>
      <cf:MaxReportedNbOccurrencesPerItem>75</cf:MaxReportedNbOccurrencesPerItem>
    </cf:ReportXML>
    <cf:ReportJSON>
      <cf:ReportPath>/Users/user/Desktop/Temp/Report.json</cf:ReportPath>
      <cf:MaxReportedNbItemsPerCategory>50</cf:MaxReportedNbItemsPerCategory>
      <cf:MaxReportedNbOccurrencesPerItem>75</cf:MaxReportedNbOccurrencesPerItem>
    </cf:ReportJSON>
  </cf:Reports>
  <cf:Flattening>
    <cf:RasterVectorBalance>75</cf:RasterVectorBalance>
    <cf:VectorResolution>300</cf:VectorResolution>
    <cf:GradientResolution>150</cf:GradientResolution>
    <cf:ConvertAllText>false</cf:ConvertAllText>
    <cf:ConvertAllStrokes>true</cf:ConvertAllStrokes>
    <cf:ClipComplexRegions>true</cf:ClipComplexRegions>
    <cf:PreserveOverprint>true</cf:PreserveOverprint>
    <cf:BlendingColorSpace Type="ICCProfile">/Library/ColorSync/Profiles/UncoatedFOGRA29.icc</cf:BlendingColorSpace>
    <cf:RemoveICCProfiles>true</cf:RemoveICCProfiles>
    <cf:ImageRecompression>
      <cf:Color>JPEGMedium</cf:Color>
      <cf:Grayscale>ZIP8bit</cf:Grayscale>
      <cf:OneBit>RunLength</cf:OneBit>
      <cf:ASCIIIFilter>ASCIIHex</cf:ASCIIIFilter>
    </cf:ImageRecompression>
  </cf:Flattening>
  <cf:Mutators>
    <cf>ActionList>/Users/user/Desktop/My Action List Collection/Add Stamp.eal</cf>ActionList>
    <cf>ActionList>/Users/user/Desktop/My Action List Collection/Rotate.eal</cf>ActionList>
  </cf:Mutators>
  <cf:SmartPreflight>
    <cf:VariableSet>/Users/user/Desktop/My Action Variable Set Collection/Page Size.evs</cf:VariableSet>
    <cf:JobTicket>/Users/user/Desktop/Desktop/Temp/JobTicket.xml</cf:JobTicket>
  </cf:SmartPreflight>
  <cf:CertifiedPDF>
    <cf:CertifiedPDFAction>MakeCertified</cf:CertifiedPDFAction>
  </cf:CertifiedPDF>
</cf:Process>

```

```

<cf:KeepOriginalProfile>>false</cf:KeepOriginalProfile>
<cf:UserInfo>
  <cf:Name>Name</cf:Name>
  <cf:Company>Company</cf:Company>
  <cf:Street>Street</cf:Street>
  <cf:City>City</cf:City>
  <cf:State>State</cf:State>
  <cf:Country>Country</cf:Country>
  <cf:PostalCode>PostalCode</cf:PostalCode>
  <cf:Phone>Phone</cf:Phone>
  <cf:Fax>Fax</cf:Fax>
  <cf:Email>Email</cf:Email>
  <cf:Message>Message</cf:Message>
</cf:UserInfo>
<cf:SessionComment>SessionComment</cf:SessionComment>
</cf:CertifiedPDF>
<cf:ColorManagement>
  <cf:Images>
    <cf:Enabled>true</cf:Enabled>
    <cf:RenderingIntent>ObjectDefined</cf:RenderingIntent>
    <cf:SourceICCProfiles>
      <cf:Gray>/Users/user/Library/ColorSync/Profiles/Source Gray.icc</cf:Gray>
      <cf:RGB>/Users/user/Library/ColorSync/Profiles/Source RGB.icc</cf:RGB>
      <cf:CMYK>/Users/user/Library/ColorSync/Profiles/SourceCMYK.icm</cf:CMYK>
      <cf:Lab>/Users/user/Library/ColorSync/Profiles/Source Lab.icc</cf:Lab>
    </cf:SourceICCProfiles>
    <cf:SourceOutputIntentOverridesICCProfiles>
      false
    </cf:SourceOutputIntentOverridesICCProfiles>
    <cf:TargetICCProfiles>
      <cf:Gray>/Users/user/Library/ColorSync/Profiles/Target Gray.icc</cf:Gray>
      <cf:RGB>/Users/user/Library/ColorSync/Profiles/Target RGB.icm</cf:RGB>
      <cf:CMYK>/Users/user/Library/ColorSync/Profiles/Target CMYK.icc</cf:CMYK>
      <cf:Lab>/Users/user/Library/ColorSync/Profiles/Target Lab.icc</cf:Lab>
    </cf:TargetICCProfiles>
    <cf:TargetOutputIntentOverridesICCProfiles>
      false
    </cf:TargetOutputIntentOverridesICCProfiles>
  </cf:Images>
  <cf:OtherObjects>
    <cf:Enabled>true</cf:Enabled>
    <cf:RenderingIntent>ObjectDefined</cf:RenderingIntent>
    <cf:SourceICCProfiles>
      <cf:Gray>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
Gray.icm</cf:Gray>
      <cf:RGB>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/AdobeRGB1998.icc</
cf:RGB>
      <cf:CMYK>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/WAN-IFRA/
ISOcoated_v2_eci.icc</cf:CMYK>
      <cf:Lab>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
Lab.icm</cf:Lab>
    </cf:SourceICCProfiles>
    <cf:SourceOutputIntentOverridesICCProfiles>
      false
    </cf:SourceOutputIntentOverridesICCProfiles>
    <cf:TargetICCProfiles>
      <cf:Gray>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
Gray.icm</cf:Gray>
      <cf:RGB>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/AdobeRGB1998.icc</
cf:RGB>
      <cf:CMYK>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/WAN-IFRA/
ISOcoated_v2_eci.icc</cf:CMYK>
      <cf:Lab>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
Lab.icm</cf:Lab>
    </cf:TargetICCProfiles>
    <cf:TargetOutputIntentOverridesICCProfiles>
      false
    </cf:TargetOutputIntentOverridesICCProfiles>
  </cf:OtherObjects>

```

```

    <cf:UseBlackPointCompensation>true</cf:UseBlackPointCompensation>
  </cf:ColorManagement>
  <cf:Fonts>
    <cf:UseSystemFonts>true</cf:UseSystemFonts>
    <cf:AdditionalFolder>/Users/user/Desktop/Collected Fonts</cf:AdditionalFolder>
  </cf:Fonts>
  <cf:Language>enUS</cf:Language>
  <cf:MeasurementUnit>Point</cf:MeasurementUnit>
</cf:Process>

<cf:ExportImage TaskID="My Render Job">
  <cf:InputPDF>
    <cf:InputPath>/Users/user/Desktop/Temp/Input.pdf</cf:InputPath>
  </cf:InputPDF>
  <cf:OutputImages>
    <cf:OutputPath>/Users/user/Desktop/Temp/Images/image%1.png</cf:OutputPath>
    <cf:SaveOptions FileType="PNG">
      <cf:Interlaced>true</cf:Interlaced>
      <cf:EmbedICCProfile>true</cf:EmbedICCProfile>
    </cf:SaveOptions>
  </cf:OutputImages>
  <cf:RenderOptions>
    <cf:RenderType>Separations</cf:RenderType>
    <cf:OutputColorSpace>DeviceGray</cf:OutputColorSpace>
    <cf:BackgroundColor>
      <cf:Gray>0.2</cf:Gray>
    </cf:BackgroundColor>
    <cf:RenderArea>BleedBox</cf:RenderArea>
    <cf:ImageDimensions>
      <cf:Width>600</cf:Width>
    </cf:ImageDimensions>
    <cf:IncludeEmptyPages>true</cf:IncludeEmptyPages>
    <cf:AntiAliasing>false</cf:AntiAliasing>
  </cf:RenderOptions>
  <cf>ActionLists>
    <cf:PrerenderActionList>/Users/user/Desktop/My Action List Collection/Add
    Watermark.eal</cf:PrerenderActionList>
    <cf:RestrictingActionList>/Users/user/Desktop/My Action List Collection/Select
    Artwork And Language Layer.eal</cf:RestrictingActionList>
  </cf>ActionLists>
  <cf:SmartPreflight>
    <cf:VariableSet>/Users/user/Desktop/My Action Variable Set Collection/Language
    Selection.evs</cf:VariableSet>
    <cf:JobTicket>/Users/user/Desktop/Temp/JobTicket.xml</cf:JobTicket>
  </cf:SmartPreflight>
  <cf:ColorManagement>
    <cf:AllObjects>
      <cf:Enabled>true</cf:Enabled>
      <cf:RenderingIntent>ObjectDefined</cf:RenderingIntent>
      <cf:SourceICCProfiles>
        <cf:Gray>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
        Gray.icm</cf:Gray>
        <cf:RGB>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/AdobeRGB1998.icc</
        cf:RGB>
        <cf:CMYK>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/WAN-IFRA/
        ISOcoated_v2_eci.icc</cf:CMYK>
        <cf:Lab>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
        Lab.icm</cf:Lab>
      </cf:SourceICCProfiles>
      <cf:SourceOutputIntentOverridesICCProfiles>
        false
      </cf:SourceOutputIntentOverridesICCProfiles>
      <cf:TargetICCProfiles>
        <cf:Gray>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus
        Gray.icm</cf:Gray>
        <cf:RGB>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/AdobeRGB1998.icc</
        cf:RGB>
        <cf:CMYK>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/
        Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/WAN-IFRA/
        ISOcoated_v2_eci.icc</cf:CMYK>
      </cf:TargetICCProfiles>
    </cf:AllObjects>
  </cf:ColorManagement>
</cf:ExportImage>

```

```
<cf:Lab>/Applications/Enfocus/Enfocus PitStop Server 24/PitStop Server.app/  
Contents/Resources/PitStopServerWatchdog.app/Contents/Resources/ICC/Generic Enfocus  
Lab.icm</cf:Lab>  
</cf:TargetICCPProfiles>  
<cf:TargetOutputIntentOverridesICCPProfiles>  
  false  
</cf:TargetOutputIntentOverridesICCPProfiles>  
</cf:AllObjects>  
<cf:UseBlackPointCompensation>true</cf:UseBlackPointCompensation>  
</cf:ColorManagement>  
<cf:Fonts>  
  <cf:UseSystemFonts>true</cf:UseSystemFonts>  
  <cf:AdditionalFolder>/Users/user/Desktop/Collected Fonts</cf:AdditionalFolder>  
</cf:Fonts>  
</cf:ExportImage>  
</cf:Configuration>
```

7. Third-Party License Information

This product includes lzw-ab.

Copyright (c) David Bryant
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Conifer Software nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes Botan.

Copyright (C) 1999-2023 The Botan Authors
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes ICC Profiles.

Some ICC Profiles were created by FFEI Ltd. (www.ffei.co.uk) using Fujifilm ColourKit Profiler Suite (www.colourprofiling.com)

This product includes ICC Profiles.

Some ICC profiles are copyright (C) by European Color Initiative, www.eci.org

This product includes ICC Profiles.

Some ICC profiles are copyright (C) of WAN-IFRA, www.wan-ifra.org

This product includes ICC Profiles.

Some ICC profiles are copyright (C) IDEAlliance(R). G7(R), GRACol(R) and SWOP(R) are all registered trademarks of IDEAlliance(C).

This product includes PANTONE Color Libraries.

PANTONE® and other Pantone trademarks are the property of Pantone LLC. Pantone is a wholly owned subsidiary of X-Rite, Incorporated.

This product includes curl.

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1996 - 2024, Daniel Stenberg, <daniel@haxx.se>, and many contributors, see the THANKS file.

All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

This product includes LibTIFF.

Copyright (c) 1988-1997 Sam Leffler
Copyright (c) 1991-1997 Silicon Graphics, Inc.

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that (i) the above copyright notices and this permission notice appear in all copies of the software and related documentation, and (ii) the names of Sam Leffler and Silicon Graphics may not be used in any advertising or publicity relating to the software without the specific, prior written permission of Sam Leffler and Silicon Graphics.

THE SOFTWARE IS PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EXPRESS, IMPLIED OR OTHERWISE, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

IN NO EVENT SHALL SAM LEFFLER OR SILICON GRAPHICS BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER OR NOT ADVISED OF THE POSSIBILITY OF DAMAGE, AND ON ANY THEORY OF LIABILITY, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

This product includes FreeType.

Portions of this software are copyright (C) 2014 The FreeType Project (www.freetype.org) licensed under the Freetype License. All rights reserved.

This product includes Google Breakpad.

Copyright (c) 2006, Google Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes curl.

Copyright (c) 1996 - 2011, Daniel Stenberg, <daniel@haxx.se>. All rights reserved.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

This product includes Google Logging Library (glog).

Copyright (c) 2008, Google Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes Protocol Buffers.

Copyright (c) 2008, Google Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes gSOAP.

EXHIBIT B.

Part of the software embedded in this product is gSOAP software.
Portions created by gSOAP are Copyright (C) 2001-2007 Robert A. van Engelen, Genivia inc. All Rights Reserved.

THE SOFTWARE IN THIS PRODUCT WAS IN PART PROVIDED BY GENIVIA INC AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes ICU.

Copyright (c) 1991-2023 Unicode, Inc. All rights reserved.
Distributed under the Terms of Use in <https://www.unicode.org/copyright.html>.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that either
(a) this copyright and permission notice appear with all copies of the Data Files or Software, or
(b) this copyright and permission notice appear in associated

Documentation.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Chinese/Japanese Word Break Dictionary Data (cjdict.txt)

```
# The Google Chrome software developed by Google is licensed under
# the BSD license. Other software included in this distribution is
# provided under other licenses, as set forth below.
#
# The BSD License
# http://opensource.org/licenses/bsd-license.php
# Copyright (C) 2006-2008, Google Inc.
#
# All rights reserved.
#
# Redistribution and use in source and binary forms, with or without
# modification, are permitted provided that the following conditions are met:
#
# Redistributions of source code must retain the above copyright notice,
# this list of conditions and the following disclaimer.
# Redistributions in binary form must reproduce the above
# copyright notice, this list of conditions and the following
# disclaimer in the documentation and/or other materials provided with
# the distribution.
# Neither the name of Google Inc. nor the names of its
# contributors may be used to endorse or promote products derived from
# this software without specific prior written permission.
#
#
# THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
# CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
# INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
# MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
# DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
# LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
# CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
# SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
# BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
# LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
# NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
# SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
#
#
# The word list in cjdict.txt are generated by combining three word lists
# listed below with further processing for compound word breaking. The
# frequency is generated with an iterative training against Google web
# corpora.
#
# * Libtabe (Chinese)
#   - https://sourceforge.net/project/?group_id=1519
#   - Its license terms and conditions are shown below.
#
# * IPADIC (Japanese)
#   - http://chasen.aist-nara.ac.jp/chasen/distribution.html
#   - Its license terms and conditions are shown below.
#
# -----COPYING.libtabe ---- BEGIN-----
#
# /*
#  * Copyright (c) 1999 TaBE Project.
#  * Copyright (c) 1999 Pai-Hsiang Hsiao.
#  * All rights reserved.
#  *
#  * Redistribution and use in source and binary forms, with or without
#  * modification, are permitted provided that the following conditions
```

```
#
# * are met:
#
# *
# * . Redistributions of source code must retain the above copyright
# * notice, this list of conditions and the following disclaimer.
# * . Redistributions in binary form must reproduce the above copyright
# * notice, this list of conditions and the following disclaimer in
# * the documentation and/or other materials provided with the
# * distribution.
# * . Neither the name of the TaBE Project nor the names of its
# * contributors may be used to endorse or promote products derived
# * from this software without specific prior written permission.
#
# *
# * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
# * "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
# * LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
# * FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
# * REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
# * INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
# * (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
# * SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
# * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
# * STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
# * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
# * OF THE POSSIBILITY OF SUCH DAMAGE.
# */
#
# /*
# * Copyright (c) 1999 Computer Systems and Communication Lab,
# * Institute of Information Science, Academia
# * Sinica. All rights reserved.
# *
# * Redistribution and use in source and binary forms, with or without
# * modification, are permitted provided that the following conditions
# * are met:
# *
# * . Redistributions of source code must retain the above copyright
# * notice, this list of conditions and the following disclaimer.
# * . Redistributions in binary form must reproduce the above copyright
# * notice, this list of conditions and the following disclaimer in
# * the documentation and/or other materials provided with the
# * distribution.
# * . Neither the name of the Computer Systems and Communication Lab
# * nor the names of its contributors may be used to endorse or
# * promote products derived from this software without specific
# * prior written permission.
# *
# * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
# * "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
# * LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
# * FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
# * REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
# * INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
# * (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
# * SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
# * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
# * STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
# * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
# * OF THE POSSIBILITY OF SUCH DAMAGE.
# */
#
# Copyright 1996 Chih-Hao Tsai @ Beckman Institute,
# University of Illinois
# c-tsai4@uiuc.edu http://casper.beckman.uiuc.edu/~c-tsai4
#
# -----COPYING.libtabe-----END-----
#
# -----COPYING.ipadic-----BEGIN-----
#
# Copyright 2000, 2001, 2002, 2003 Nara Institute of Science
# and Technology. All Rights Reserved.
#
# Use, reproduction, and distribution of this software is permitted.
# Any copy of this software, whether in its original form or modified,
# must include both the above copyright notice and the following
# paragraphs.
#
```

```

# Nara Institute of Science and Technology (NAIST),
# the copyright holders, disclaims all warranties with regard to this
# software, including all implied warranties of merchantability and
# fitness, in no event shall NAIST be liable for
# any special, indirect or consequential damages or any damages
# whatsoever resulting from loss of use, data or profits, whether in an
# action of contract, negligence or other tortuous action, arising out
# of or in connection with the use or performance of this software.
#
# A large portion of the dictionary entries
# originate from ICOT Free Software. The following conditions for ICOT
# Free Software applies to the current dictionary as well.
#
# Each User may also freely distribute the Program, whether in its
# original form or modified, to any third party or parties, PROVIDED
# that the provisions of Section 3 ("NO WARRANTY") will ALWAYS appear
# on, or be attached to, the Program, which is distributed substantially
# in the same form as set out herein and that such intended
# distribution, if actually made, will neither violate or otherwise
# contravene any of the laws and regulations of the countries having
# jurisdiction over the User or the intended distribution itself.
#
# NO WARRANTY
#
# The program was produced on an experimental basis in the course of the
# research and development conducted during the project and is provided
# to users as so produced on an experimental basis. Accordingly, the
# program is provided without any warranty whatsoever, whether express,
# implied, statutory or otherwise. The term "warranty" used herein
# includes, but is not limited to, any warranty of the quality,
# performance, merchantability and fitness for a particular purpose of
# the program and the nonexistence of any infringement or violation of
# any right of any third party.
#
# Each user of the program will agree and understand, and be deemed to
# have agreed and understood, that there is no warranty whatsoever for
# the program and, accordingly, the entire risk arising from or
# otherwise connected with the program is assumed by the user.
#
# Therefore, neither ICOT, the copyright holder, or any other
# organization that participated in or was otherwise related to the
# development of the program and their respective officials, directors,
# officers and other employees shall be held liable for any and all
# damages, including, without limitation, general, special, incidental
# and consequential damages, arising out of or otherwise in connection
# with the use or inability to use the program or any product, material
# or result produced or otherwise obtained by using the program,
# regardless of whether they have been advised of, or otherwise had
# knowledge of, the possibility of such damages at any time during the
# project or thereafter. Each user will be deemed to have agreed to the
# foregoing by his or her commencement of use of the program. The term
# "use" as used herein includes, but is not limited to, the use,
# modification, copying and distribution of the program and the
# production of secondary products from the program.
#
# In the case where the program, whether in its original form or
# modified, was distributed or delivered to or received by a user from
# any person, organization or entity other than ICOT, unless it makes or
# grants independently of ICOT any specific warranty to the user in
# writing, such person, organization or entity, will also be exempted
# from and not be held liable to the user for any such damages as noted
# above as far as the program is concerned.
#
# -----COPYING.ipadic-----END-----

```

Lao Word Break Dictionary Data (laodict.txt)

```

# Copyright (C) 2016 and later: Unicode, Inc. and others.
# License & terms of use: http://www.unicode.org/copyright.html
# Copyright (c) 2015 International Business Machines Corporation
# and others. All Rights Reserved.
#
# Project: https://github.com/rober42539/lao-dictionary
# Dictionary: https://github.com/rober42539/lao-dictionary/laodict.txt
# License: https://github.com/rober42539/lao-dictionary/LICENSE.txt

```

```

# (copied below)
#
# This file is derived from the above dictionary version of Nov 22, 2020
# -----
# Copyright (C) 2013 Brian Eugene Wilson, Robert Martin Campbell.
# All rights reserved.
#
# Redistribution and use in source and binary forms, with or without
# modification, are permitted provided that the following conditions are met:
#
# Redistributions of source code must retain the above copyright notice, this
# list of conditions and the following disclaimer. Redistributions in binary
# form must reproduce the above copyright notice, this list of conditions and
# the following disclaimer in the documentation and/or other materials
# provided with the distribution.
#
# THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
# "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
# LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
# FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
# COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
# INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
# (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
# SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
# HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
# STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
# ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
# OF THE POSSIBILITY OF SUCH DAMAGE.
# -----

-----

Burmese Word Break Dictionary Data (burmesedict.txt)

# Copyright (c) 2014 International Business Machines Corporation
# and others. All Rights Reserved.
#
# This list is part of a project hosted at:
#   github.com/kanyawtech/myanmar-karen-word-lists
#
# -----
# Copyright (c) 2013, LeRoy Benjamin Sharon
# All rights reserved.
#
# Redistribution and use in source and binary forms, with or without
# modification, are permitted provided that the following conditions
# are met: Redistributions of source code must retain the above
# copyright notice, this list of conditions and the following
# disclaimer. Redistributions in binary form must reproduce the
# above copyright notice, this list of conditions and the following
# disclaimer in the documentation and/or other materials provided
# with the distribution.
#
# Neither the name Myanmar Karen Word Lists, nor the names of its
# contributors may be used to endorse or promote products derived
# from this software without specific prior written permission.
#
# THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
# CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
# INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
# MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
# DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS
# BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
# EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
# TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
# DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
# ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
# TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF
# THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
# SUCH DAMAGE.
# -----

-----

Time Zone Database

ICU uses the public domain data and code derived from Time Zone

```

Database for its time zone support. The ownership of the TZ database is explained in BCP 175: Procedure for Maintaining the Time Zone Database section 7.

```
# 7. Database Ownership
#
# The TZ database itself is not an IETF Contribution or an IETF
# document. Rather it is a pre-existing and regularly updated work
# that is in the public domain, and is intended to remain in the
# public domain. Therefore, BCPs 78 [RFC5378] and 79 [RFC3979] do
# not apply to the TZ Database or contributions that individuals make
# to it. Should any claims be made and substantiated against the TZ
# Database, the organization that is providing the IANA
# Considerations defined in this RFC, under the memorandum of
# understanding with the IETF, currently ICANN, may act in accordance
# with all competent court orders. No ownership claims will be made
# by ICANN or the IETF Trust on the database or the code. Any person
# making a contribution to the database or code waives all rights to
# future claims in that contribution or in the TZ Database.
```

Google double-conversion

Copyright 2006-2011, the V8 project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

File: aclocal.m4 (only for ICU4C)
Section: pkg.m4 - Macros to locate and utilise pkg-config.

Copyright (c) 2004 Scott James Remnant <scott@netsplit.com>.
Copyright (c) 2012-2015 Dan Nicholson <dbn.lists@gmail.com>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

As a special exception to the GNU General Public License, if you distribute this file as part of a program that contains a

configuration script generated by Autoconf, you may include it under the same distribution terms that you use for the rest of that program.

(The condition for the exception is fulfilled because ICU4C includes a configuration script generated by Autoconf, namely the `configure` script.)

File: config.guess (only for ICU4C)

This file is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, see <<https://www.gnu.org/licenses/>>.

As a special exception to the GNU General Public License, if you distribute this file as part of a program that contains a configuration script generated by Autoconf, you may include it under the same distribution terms that you use for the rest of that program. This Exception is an additional permission under section 7 of the GNU General Public License, version 3 ("GPLv3").

(The condition for the exception is fulfilled because ICU4C includes a configuration script generated by Autoconf, namely the `configure` script.)

File: install-sh (only for ICU4C)

Copyright 1991 by the Massachusetts Institute of Technology

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of M.I.T. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

This product includes JBIG2Lib.

Portions of this product copyrights (C) 2002 Glyph & Cog, LLC.

This product includes JPEGLib.

This software is copyright (C) 1991-2016, Thomas G. Lane, Guido Vollbeding.
All Rights Reserved.

This software is based in part on the work of the Independent JPEG Group.

This product includes Little CMS.

Little CMS
Copyright (c) 2023 Marti Maria Saguer

Permission is hereby granted, free of charge, to any person obtaining

a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

This product includes libxml2.

Copyright (C) 1998-2012 Daniel Veillard. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

This product includes IP*Works!.

Copyright (c) 2017 /n software inc. - All rights reserved.

DISCLAIMER OF WARRANTY. THE LICENSED SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. FURTHER, /N SOFTWARE SPECIFICALLY DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE LICENSED SOFTWARE OR DOCUMENTATION IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, CURRENTNESS, OR OTHERWISE. THE ENTIRE RISK AS TO THE RESULTS AND PERFORMANCE OF THE LICENSED SOFTWARE IS ASSUMED BY YOU. NO ORAL OR WRITTEN INFORMATION OR ADVICE GIVEN BY /N SOFTWARE OR ITS EMPLOYEES SHALL CREATE A WARRANTY OR IN ANY WAY INCREASE THE SCOPE OF THIS WARRANTY, AND YOU MAY NOT RELY ON ANY SUCH INFORMATION OR ADVICE. FURTHER, THE LICENSED SOFTWARE IS NOT FAULT-TOLERANT AND IS NOT DESIGNED, MANUFACTURED OR INTENDED FOR USE OR RESALE AS ON-LINE CONTROL EQUIPMENT IN HAZARDOUS ENVIRONMENTS REQUIRING FAIL-SAFE PERFORMANCE, SUCH AS IN THE OPERATION OF NUCLEAR FACILITIES, AIRCRAFT NAVIGATION OR COMMUNICATION SYSTEMS, AIR TRAFFIC CONTROL, DIRECT LIFE SUPPORT MACHINES, OR WEAPONS SYSTEMS, IN WHICH THE FAILURE OF THE LICENSED SOFTWARE COULD LEAD DIRECTLY TO DEATH, PERSONAL INJURY, OR SEVERE PHYSICAL OR ENVIRONMENTAL DAMAGE ("HIGH RISK ACTIVITIES"). /N SOFTWARE AND ITS SUPPLIERS SPECIFICALLY DISCLAIM ANY EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR HIGH RISK ACTIVITIES.

LIMITATION ON LIABILITY. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT WILL /N SOFTWARE'S TOTAL AGGREGATE AND CUMULATIVE LIABILITY TO YOU FOR ANY AND ALL CLAIMS OF ANY KIND ARISING HEREUNDER EXCEED THE AMOUNT OF LICENSE FEES ACTUALLY PAID BY YOU FOR THE LICENSED SOFTWARE GIVING RISE TO THE CLAIM IN THE TWELVE MONTHS PRECEDING THE CLAIM. /N SOFTWARE'S LICENSORS AND THEIR SUPPLIERS SHALL HAVE NO LIABILITY TO YOU FOR ANY DAMAGES SUFFERED BY YOU OR ANY THIRD PARTY AS A RESULT OF USING THE LICENSED SOFTWARE, OR ANY PORTION THEREOF. NOTWITHSTANDING THE FOREGOING, IN NO EVENT SHALL /N SOFTWARE, ITS LICENSORS, OR ANY OF THEIR RESPECTIVE SUPPLIERS BE LIABLE FOR ANY LOST REVENUE, PROFIT OR DATA, OR FOR INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER, INCLUDING, WITHOUT LIMITATION, ANY COMMERCIAL DAMAGES OR LOSSES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF

LIABILITY, ARISING OUT OF THE USE OR INABILITY TO USE THE LICENSED SOFTWARE, OR ANY PORTION THEREOF, EVEN IF /N SOFTWARE, ITS LICENSORS AND/OR ANY OF THEIR RESPECTIVE SUPPLIERS HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY. EACH EXCLUSION OF LIMITATION IS INTENDED TO BE SEPARATE AND THEREFORE SEVERABLE.

This product includes IP*Works! SSH.

Copyright (c) 2017 /n software inc. - All rights reserved.

DISCLAIMER OF WARRANTY. THE LICENSED SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. FURTHER, /N SOFTWARE SPECIFICALLY DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE LICENSED SOFTWARE OR DOCUMENTATION IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, CURRENTNESS, OR OTHERWISE. THE ENTIRE RISK AS TO THE RESULTS AND PERFORMANCE OF THE LICENSED SOFTWARE IS ASSUMED BY YOU. NO ORAL OR WRITTEN INFORMATION OR ADVICE GIVEN BY /N SOFTWARE OR ITS EMPLOYEES SHALL CREATE A WARRANTY OR IN ANY WAY INCREASE THE SCOPE OF THIS WARRANTY, AND YOU MAY NOT RELY ON ANY SUCH INFORMATION OR ADVICE. FURTHER, THE LICENSED SOFTWARE IS NOT FAULT-TOLERANT AND IS NOT DESIGNED, MANUFACTURED OR INTENDED FOR USE OR RESALE AS ON-LINE CONTROL EQUIPMENT IN HAZARDOUS ENVIRONMENTS REQUIRING FAIL-SAFE PERFORMANCE, SUCH AS IN THE OPERATION OF NUCLEAR FACILITIES, AIRCRAFT NAVIGATION OR COMMUNICATION SYSTEMS, AIR TRAFFIC CONTROL, DIRECT LIFE SUPPORT MACHINES, OR WEAPONS SYSTEMS, IN WHICH THE FAILURE OF THE LICENSED SOFTWARE COULD LEAD DIRECTLY TO DEATH, PERSONAL INJURY, OR SEVERE PHYSICAL OR ENVIRONMENTAL DAMAGE ("HIGH RISK ACTIVITIES"). /N SOFTWARE AND ITS SUPPLIERS SPECIFICALLY DISCLAIM ANY EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR HIGH RISK ACTIVITIES.

LIMITATION ON LIABILITY. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, IN NO EVENT WILL /N SOFTWARE'S TOTAL AGGREGATE AND CUMULATIVE LIABILITY TO YOU FOR ANY AND ALL CLAIMS OF ANY KIND ARISING HEREUNDER EXCEED THE AMOUNT OF LICENSE FEES ACTUALLY PAID BY YOU FOR THE LICENSED SOFTWARE GIVING RISE TO THE CLAIM IN THE TWELVE MONTHS PRECEDING THE CLAIM. /N SOFTWARE'S LICENSORS AND THEIR SUPPLIERS SHALL HAVE NO LIABILITY TO YOU FOR ANY DAMAGES SUFFERED BY YOU OR ANY THIRD PARTY AS A RESULT OF USING THE LICENSED SOFTWARE, OR ANY PORTION THEREOF. NOTWITHSTANDING THE FOREGOING, IN NO EVENT SHALL /N SOFTWARE, ITS LICENSORS, OR ANY OF THEIR RESPECTIVE SUPPLIERS BE LIABLE FOR ANY LOST REVENUE, PROFIT OR DATA, OR FOR INDIRECT, PUNITIVE, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER, INCLUDING, WITHOUT LIMITATION, ANY COMMERCIAL DAMAGES OR LOSSES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF THE USE OR INABILITY TO USE THE LICENSED SOFTWARE, OR ANY PORTION THEREOF, EVEN IF /N SOFTWARE, ITS LICENSORS AND/OR ANY OF THEIR RESPECTIVE SUPPLIERS HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY. EACH EXCLUSION OF LIMITATION IS INTENDED TO BE SEPARATE AND THEREFORE SEVERABLE.

This product includes OpenJPEG.

The copyright in this software is being made available under the 2-clauses BSD License, included below. This software may be subject to other third party and contributor rights, including patent rights, and no such rights are granted under this license.

Copyright (c) 2002-2014, Universite catholique de Louvain (UCL), Belgium
Copyright (c) 2002-2014, Professor Benoit Macq
Copyright (c) 2003-2014, Antonin Descampe
Copyright (c) 2003-2009, Francois-Olivier Devaux
Copyright (c) 2005, Herve Drolon, FreeImage Team
Copyright (c) 2002-2003, Yannick Verschuere
Copyright (c) 2001-2003, David Janssens
Copyright (c) 2011-2012, Centre National d'Etudes Spatiales (CNES), France
Copyright (c) 2012, CS Systemes d'Information, France

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the

documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS 'AS IS' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes OpenSSL.

Apache License
Version 2.0, January 2004
<https://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.
4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
 - (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
 - (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
 - (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
 - (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.
9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

This product includes Enfocus PDF technology.

"Convert fill to stroke" Action, Patent Pending

This product includes Potrace.

Copyright (c) 2001-2019 Icosasoft Software Inc. All rights reserved.

This product includes Qt.

The software uses Qt, licensed under LGPL v3. The Qt Toolkit is Copyright (C) 2024 The Qt Company Ltd.

Portions of this software are copyright (C) 2006-2023 The FreeType Project (www.freetype.org). All rights reserved.

Copyright (C) 1991-2020, Thomas G. Lane, Guido Vollbeding.
This software is based in part on the work of the Independent JPEG Group.

Secure Hash Algorithm SHA-3 - brg_endian
Copyright (c) 1998-2013, Brian Gladman, Worcester, UK. All rights reserved.

LICENSE TERMS

The redistribution and use of this software (with or without changes) is allowed without the payment of fees or royalties provided that:

1. source code distributions include the above copyright notice, this list of conditions and the following disclaimer;

2. binary distributions include the above copyright notice, this list of conditions and the following disclaimer in their documentation;
3. the name of the copyright holder is not used to endorse products built using this software without specific written permission.

DISCLAIMER

This software is provided 'as is' with no explicit or implied warranties in respect of its properties, including, but not limited to, correctness and/or fitness for purpose.

This product includes QtSingleApplication.

Copyright (C) 2013 Digia Plc and/or its subsidiary(-ies).
Contact: <http://www.qt-project.org/legal>

This file is part of the Qt Solutions component.

You may use this file under the terms of the BSD license as follows:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Digia Plc and its Subsidiary(-ies) nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes LibTIFF.

Copyright (c) 1988-1997 Sam Leffler
Copyright (c) 1991-1997 Silicon Graphics, Inc.

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that (i) the above copyright notices and this permission notice appear in all copies of the software and related documentation, and (ii) the names of Sam Leffler and Silicon Graphics may not be used in any advertising or publicity relating to the software without the specific, prior written permission of Sam Leffler and Silicon Graphics.

THE SOFTWARE IS PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EXPRESS, IMPLIED OR OTHERWISE, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

IN NO EVENT SHALL SAM LEFFLER OR SILICON GRAPHICS BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER OR NOT ADVISED OF THE POSSIBILITY OF DAMAGE, AND ON ANY THEORY OF LIABILITY, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

This product includes XMP Toolkit.
Copyright (c) 2020, Adobe
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes zlib.

(C) 1995-2013 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

This product includes ZXing C++ Library.

Copyright 2016-2023 ZXing authors.
<https://github.com/zxing>

8. Copyrights

© 2024 Enfocus BV all rights reserved. Enfocus is an Esko company.

Certified PDF is a registered trademark of Enfocus BV.

Enfocus PitStop Pro, Enfocus PitStop Workgroup Manager, Enfocus PitStop Server, Enfocus BoardingPass, Enfocus Connect YOU, Enfocus Connect ALL, Enfocus Connect SEND, Enfocus StatusCheck, Enfocus CertifiedPDF.net, Enfocus PDF Workflow Suite, Enfocus Switch, Enfocus SwitchClient, Enfocus SwitchScripter, Enfocus TestDrive, Enfocus SwitchScriptTool, Enfocus Browser, PitStop Library Container, Enfocus Griffin, Enfocus Review, Enfocus FastLane and Enfocus Appstore are product names of Enfocus BV.

Adobe, Acrobat, Distiller, InDesign, Illustrator, Photoshop, FrameMaker, PDFWriter, PageMaker, Adobe PDF Library™, the Adobe logo, the Acrobat logo and PostScript are trademarks of Adobe Systems Incorporated.

Datalogics, the Datalogics logo, PDF2IMG™ and DLE™ are trademarks of Datalogics, Inc.

Apple, Mac, macOS, Macintosh, iPad and ColorSync are trademarks of Apple Computer, Inc. registered in the U.S. and other countries. Windows and Windows Server are registered trademarks of Microsoft Corporation.

PANTONE® Colors displayed here may not match PANTONE-identified standards. Consult current PANTONE Color Publications for accurate color. PANTONE® and other Pantone, Inc. trademarks are the property of Pantone, Inc. ©Pantone, Inc., 2006.

OPI is a trademark of Aldus Corporation.

Quark, QuarkXPress, QuarkXTensions, XTensions and the XTensions logo among others, are trademarks of Quark, Inc. and all applicable affiliated companies, Reg. U.S. Pat. & Tm. Off. and in many other countries.

Docker and the Docker logo are trademarks or registered trademarks of Docker, Inc. in the United States and/or other countries. Docker, Inc. and other parties may also have trademark rights in other terms used herein.

This product and use of this product is under license from Markzware under U.S. Patent No. 5,963,641.

Other brand and product names may be trademarks or registered trademarks of their respective holders. All specifications, terms and descriptions of products and services are subject to change without notice or recourse.